

IPsecME Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: March 7, 2011

Y. Nir, Ed.  
Check Point  
D. Wierbowski  
IBM  
September 3, 2010

A Quick Crash Detection Method for IKE  
draft-ietf-ipsecme-failure-detection-00

Abstract

This document describes an extension to the IKEv2 protocol that allows for faster detection of SA desynchronization using a saved token.

When an IPsec tunnel between two IKEv2 peers is disconnected due to a restart of one peer, it can take as much as several minutes for the other peer to discover that the reboot has occurred, thus delaying recovery. In this text we propose an extension to the protocol, that allows for recovery immediately following the restart.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 7, 2011.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction	4
1.1. Conventions Used in This Document	4
2. RFC 4306 Crash Recovery	5
3. Protocol Outline	5
4. Formats and Exchanges	6
4.1. Notification Format	6
4.2. Passing a Token in the AUTH Exchange	7
4.3. Replacing Tokens After Rekey or Resumption	9
4.4. Replacing the Token for an Existing SA	9
4.5. Presenting the Token in an INFORMATIONAL Exchange	10
5. Token Generation and Verification	11
5.1. A Stateless Method of Token Generation	11
5.2. A Stateless Method with IP addresses	12
5.3. Token Lifetime	12
6. Backup Gateways	12
7. Alternative Solutions	13
7.1. Initiating a new IKE SA	13
7.2. SIR	13
7.3. Birth Certificates	13
7.4. Reducing Liveness Check Length	14
8. Interaction with Session Resumption	14
9. Operational Considerations	16
9.1. Who should implement this specification	16
9.2. Response to unknown child SPI	17
9.3. Using Tokens that Depend on IP Addresses	17
10. Security Considerations	18
10.1. QCD Token Generation and Handling	18
10.2. QCD Token Transmission	19
10.3. QCD Token Enumeration	19
11. IANA Considerations	20
12. Acknowledgements	20
13. Change Log	20
13.1. Changes from draft-nir-ike-qcd-07	20
13.2. Changes from draft-nir-ike-qcd-03 and -04	20
13.3. Changes from draft-nir-ike-qcd-02	20
13.4. Changes from draft-nir-ike-qcd-01	21
13.5. Changes from draft-nir-ike-qcd-00	21
13.6. Changes from draft-nir-qcr-00	21
14. References	21
14.1. Normative References	21
14.2. Informative References	22
Authors' Addresses	22

## 1. Introduction

IKEv2, as described in [IKEv2bis] and its predecessor RFC 4306, has a method for recovering from a reboot of one peer. As long as traffic flows in both directions, the rebooted peer should re-establish the tunnels immediately. However, in many cases the rebooted peer is a VPN gateway that protects only servers, or else the non-rebooted peer has a dynamic IP address. In such cases, the rebooted peer will not be able to re-establish the tunnels. Section 2 describes how recovery works under RFC 4306, and explains why it may take several minutes.

The method proposed here, is to send an octet string, called a "QCD token" in the IKE\_AUTH exchange that establishes the tunnel. That token can be stored on the peer as part of the IKE SA. After a reboot, the rebooted implementation can re-generate the token, and send it to the peer, so as to delete the IKE SA. Deleting the IKE SA results in a quick establishment of new IPsec tunnels. This is described in Section 3.

### 1.1. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

The term "token" refers to an octet string that an implementation can generate using only the properties of a protected IKE message (such as IKE SPIs) as input. A conforming implementation **MUST** be able to generate the same token from the same input even after rebooting.

The term "token maker" refers to an implementation that generates a token and sends it to the peer as specified in this document.

The term "token taker" refers to an implementation that stores such a token or a digest thereof, in order to verify that a new token it receives is identical to the old token it has stored.

The term "non-volatile storage" in this document refers to a data storage module, that persists across restarts of the token maker. Examples of such a storage module include an internal disk, an internal flash memory module, an external disk and an external database. A small non-volatile storage module is required for a token maker, but a larger one can be used to enhance performance, as described in Section 9.2.

## 2. RFC 4306 Crash Recovery

When one peer loses state or reboots, the other peer does not get any notification, so unidirectional IPsec traffic can still flow. The rebooted peer will not be able to decrypt it, however, and the only remedy is to send an unprotected INVALID\_SPI notification as described in section 3.10.1 of [IKEv2bis]. That section also describes the processing of such a notification:

"If this Informational Message is sent outside the context of an IKE\_SA, it should be used by the recipient only as a "hint" that something might be wrong (because it could easily be forged)."

XML2PDFRFC-ENDARTWORK

Since the INVALID\_SPI can only be used as a hint, the non-rebooted peer has to determine whether the IPsec SA, and indeed the parent IKE SA are still valid. The method of doing this is described in section 2.4 of [IKEv2bis]. This method, called "liveness check" involves sending a protected empty INFORMATIONAL message, and awaiting a response. This procedure is sometimes referred to as "Dead Peer Detection" or DPD.

Section 2.4 does not mandate how many times the liveness check message should be retransmitted, or for how long, but does recommend the following:

"It is suggested that messages be retransmitted at least a dozen times over a period of at least several minutes before giving up on an SA..."

XML2PDFRFC-ENDARTWORK

Those "at least several minutes" are a time during which both peers are active, but IPsec cannot be used.

## 3. Protocol Outline

Supporting implementations will send a notification, called a "QCD token", as described in Section 4.1 in the last IKE\_AUTH exchange messages. These are the final IKE\_AUTH request and final IKE\_AUTH response that contain the AUTH payloads. The generation of these tokens is a local matter for implementations, but considerations are described in Section 5. Implementations that send such a token will be called "token makers".

A supporting implementation receiving such a token MUST store it (or a digest thereof) along with the IKE SA. Implementations that

support this part of the protocol will be called "token takers". Section 9.1 has considerations for which implementations need to be token takers, and which should be token makers. Implementation that are not token takers will silently ignore QCD tokens.

When a token maker receives a protected IKE request message with unknown IKE SPIs, it SHOULD generate a new token that is identical to the previous token, and send it to the requesting peer in an unprotected IKE message as described in Section 4.5.

When a token taker receives the QCD token in an unprotected notification, it MUST verify that the `TOKEN_SECRET_DATA` matches the token stored with the matching IKE SA. If the verification fails, or if the IKE SPIs in the message do not match any existing IKE SA, it SHOULD log the event. If it succeeds, it MUST silently delete the IKE SA associated with the `IKE_SPI` fields, and all dependant child SAs. This event MAY also be logged. The token taker MUST accept such tokens from any IP address and port combination, so as to allow different kinds of high-availability configurations of the token maker.

A supporting token taker MAY immediately create new SAs using an Initial exchange, or it may wait for subsequent traffic to trigger the creation of new SAs.

See Section 8 for a short discussion about this extensions' interaction with IKEv2 Session Resumption ([RFC5723]).

#### 4. Formats and Exchanges

##### 4.1. Notification Format

The notification payload called "QCD token" is formatted as follows:

```

          1                2                3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
    +-----+-----+-----+-----+-----+-----+-----+-----+
    ! Next Payload !C!  RESERVED   !           Payload Length      !
    +-----+-----+-----+-----+-----+-----+-----+-----+
    ! Protocol ID  !  SPI Size    ! QCD Token Notify Message Type !
    +-----+-----+-----+-----+-----+-----+-----+-----+
    !
    ~                               TOKEN_SECRET_DATA                ~
    !
    +-----+-----+-----+-----+-----+-----+-----+-----+
    XML2PDFRFC-ENDARTWORK
  
```

- o Protocol ID (1 octet) MUST be 1, as this message is related to an IKE SA.
- o SPI Size (1 octet) MUST be zero, in conformance with section 3.10 of [IKEv2bis].
- o QCD Token Notify Message Type (2 octets) - MUST be xxxxx, the value assigned for QCD token notifications. TBA by IANA.
- o TOKEN\_SECRET\_DATA (16-128 octets) contains a generated token as described in Section 5.

#### 4.2. Passing a Token in the AUTH Exchange

For brevity, only the EAP version of an AUTH exchange will be presented here. The non-EAP version is very similar. The figures below are based on appendix C.3 of [IKEv2bis].

```

first request      --> IDi,
                   [N(INITIAL_CONTACT)],
                   [[N(HTTP_CERT_LOOKUP_SUPPORTED)], CERTREQ+],
                   [IDr],
                   [CP(CFG_REQUEST)],
                   [N(IPCOMP_SUPPORTED)+],
                   [N(USE_TRANSPORT_MODE)],
                   [N(ESP_TFC_PADDING_NOT_SUPPORTED)],
                   [N(NON_FIRST_FRAGMENTS_ALSO)],
                   SA, TSi, TSr,
                   [V+]

first response    <-- IDr, [CERT+], AUTH,
                   EAP,
                   [V+]

repeat 1..N times / --> EAP
                  |
                  \ <-- EAP

last request      --> AUTH
                   [N(QCD_TOKEN)]

last response     <-- AUTH,
                   [N(QCD_TOKEN)]
                   [CP(CFG_REPLY)],
                   [N(IPCOMP_SUPPORTED)],
                   [N(USE_TRANSPORT_MODE)],
                   [N(ESP_TFC_PADDING_NOT_SUPPORTED)],
                   [N(NON_FIRST_FRAGMENTS_ALSO)],
                   SA, TSi, TSr,
                   [N(ADDITIONAL_TS_POSSIBLE)],
                   [V+]

```

XML2PDFRFC-ENDARTWORK

Note that the QCD\_TOKEN notification is marked as optional because it is not required by this specification that every implementation be both token maker and token taker. If only one peer sends the QCD token, then a reboot of the other peer will not be recoverable by this method. This may be acceptable if traffic typically originates from the other peer.

In any case, the lack of a QCD\_TOKEN notification MUST NOT be taken as an indication that the peer does not support this standard. Conversely, if a peer does not understand this notification, it will simply ignore it. Therefore a peer MAY send this notification freely, even if it does not know whether the other side supports it.



The QCD\_TOKEN notification is related to the IKE SA and MUST follow the AUTH payload and precede the Configuration payload and all payloads related to the child SA.

#### 4.3. Replacing Tokens After Rekey or Resumption

After rekeying an IKE SA, the IKE SPIs are replaced, so the new SA also needs to have a token. If only the responder in the rekey exchange is the token maker, this can be done within the CREATE\_CHILD\_SA exchange. If the initiator is a token maker, then we need an extra informational exchange.

The following figure shows the CREATE\_CHILD\_SA exchange for rekeying the IKE SA. Only the responder sends a QCD token.

```

request          --> SA, Ni, [KEi]

response         <-- SA, Nr, [KEr], N(QCD_TOKEN)
                XML2PDFRFC-ENDARTWORK

```

If the initiator is also a token maker, it SHOULD soon initiate an INFORMATIONAL exchange as follows:

```

request          --> N(QCD_TOKEN)

response         <--
                XML2PDFRFC-ENDARTWORK

```

For session resumption, as specified in [RFC5723], the situation is similar. The responder, which is necessarily the peer that has crashed, SHOULD send a new ticket within the protected payload of the IKE\_SESSION\_RESUME exchange. If the Initiator is also a token maker, it needs to send a QCD\_TOKEN in a separate INFORMATIONAL exchange.

The INFORMATIONAL exchange described in this section can also be used if QCD tokens need to be replaced due to a key rollover. However, since token takers are required to verify at least 4 QCD tokens, this is only necessary if secret QCD keys are rolled over more than four times as often as IKE SAs are rekeyed.

#### 4.4. Replacing the Token for an Existing SA

With some token generation methods, such as that described in Section 5.2, a QCD token may sometimes become invalid, although the IKE SA is still perfectly valid.

In such a case, the token maker MUST send the new token in a protected message under that IKE SA. That exchange could be a simple

INFORMATIONAL, such as in the last figure in the previous section, or else it can be part of a MOBIKE INFORMATIONAL exchange such as in the following figure taken from section 2.2 of [RFC4555] and modified by adding a QCD\_TOKEN notification:

```
(IP_I2:4500 -> IP_R1:4500)
HDR, SK { N(UPDATE_SA_ADDRESSES),
          N(NAT_DETECTION_SOURCE_IP),
          N(NAT_DETECTION_DESTINATION_IP) } -->

<-- (IP_R1:4500 -> IP_I2:4500)
      HDR, SK { N(NAT_DETECTION_SOURCE_IP),
              N(NAT_DETECTION_DESTINATION_IP) }

<-- (IP_R1:4500 -> IP_I2:4500)
      HDR, SK { N(COOKIE2), [N(QCD_TOKEN)] }

(IP_I2:4500 -> IP_R1:4500)
HDR, SK { N(COOKIE2), [N(QCD_TOKEN)] } -->
      XML2PDFRFC-ENDARTWORK
```

A token taker MUST accept such gratuitous QCD\_TOKEN notifications as long as they are carried in protected exchanges. A token maker SHOULD NOT generate them unless it is no longer able to generate the old QCD\_TOKEN.

#### 4.5. Presenting the Token in an INFORMATIONAL Exchange

This QCD\_TOKEN notification is unprotected, and is sent as a response to a protected IKE request, which uses an IKE SA that is unknown.

```
request --> N(INVALID_IKE_SPI), N(QCD_TOKEN)+
      XML2PDFRFC-ENDARTWORK
```

If child SPIs are persistently mapped to IKE SPIs as described in Section 9.2, a token taker may get the following unprotected message in response to an ESP or AH packet.

```
request --> N(INVALID_SPI), N(QCD_TOKEN)+
      XML2PDFRFC-ENDARTWORK
```

The QCD\_TOKEN and INVALID\_IKE\_SPI notifications are sent together to support both implementations that conform to this specification and implementations that don't. Similar to the description in section 2.21 of [IKEv2bis], The IKE SPI and message ID fields in the packet headers are taken from the protected IKE request.

To support a periodic rollover of the secret used for token

generation, the token taker MUST support at least four QCD\_TOKEN notifications in a single packet. The token is considered verified if any of the QCD\_TOKEN notifications matches. The token maker MAY generate up to four QCD\_TOKEN notifications, based on several generations of keys.

If the QCD\_TOKEN verifies OK, an empty response MUST be sent. If the QCD\_TOKEN cannot be validated, a response MUST NOT be sent. Section 5 defines token verification.

## 5. Token Generation and Verification

No token generation method is mandated by this document. Two methods are documented in the following sub-sections, but they only serve as examples.

The following lists the requirements from a token generation mechanism:

- o Tokens MUST be at least 16 octets long, and no more than 128 octets long, to facilitate storage and transmission. Tokens SHOULD be indistinguishable from random data.
- o It should not be possible for an external attacker to guess the QCD token generated by an implementation. Cryptographic mechanisms such as PRNG and hash functions are RECOMMENDED.
- o The token maker, MUST be able to re-generate or retrieve the token based on the IKE SPIs even after it reboots.
- o The method of token generation MUST be such, that a collision of QCD tokens between different pairs of IKE SPI will be highly unlikely.

### 5.1. A Stateless Method of Token Generation

This describes a stateless method of generating a token:

- o At installation or immediately after the first boot of the token maker, 32 random octets are generated using a secure random number generator or a PRNG.
- o Those 32 bytes, called the "QCD\_SECRET", are stored in non-volatile storage on the machine, and kept indefinitely.
- o If key rollover is required by policy, the implementation MAY periodically generate a new QCD\_SECRET and keep up to 3 previous generations. When sending an unprotected QCD\_TOKEN, as many as 4 notification payloads may be sent, each from a different QCD\_SECRET.
- o The TOKEN\_SECRET\_DATA is calculated as follows:

```
TOKEN_SECRET_DATA = HASH(QCD_SECRET | SPI-I | SPI-R)
```

```
XML2PDFRFC-ENDARTWORK
```

### 5.2. A Stateless Method with IP addresses

This method is similar to the one in the previous section, except that the IP address of the token taker is also added to the block being hashed. This has the disadvantage that the token needs to be replaced (as described in Section 4.4) whenever the token taker changes its address.

The reason to use this method is described in Section 9.3. When using this method, the `TOKEN_SECRET_DATA` field is calculated as follows:

```
TOKEN_SECRET_DATA = HASH(QCD_SECRET | SPI-I | SPI-R | IPAddr-T)
```

```
XML2PDFRFC-ENDARTWORK
```

The `IPAddr-T` field specifies the IP address of the token taker. Secret rollover considerations are similar to those in the previous section.

### 5.3. Token Lifetime

The token is associated with a single IKE SA, and SHOULD be deleted by the token taker when the SA is deleted or expires. More formally, the token is associated with the pair (SPI-I, SPI-R).

## 6. Backup Gateways

Making crash detection and recovery quick is a worthy goal, but since rebooting a gateway takes a non-zero amount of time, many implementations choose to have a stand-by gateway ready to take over as soon as the primary gateway fails for any reason. [cluster] describes consideration for such clusters of gateways with synchronized state, but the rest of this section is relevant even when there is no synchnorized state.

If such a configuration is available, it is RECOMMENDED that the stand-by gateway be able to generate the same token as the active gateway. if the method described in Section 5.1 is used, this means that the `QCD_SECRET` field is identical in both gateways. This has

the effect of having the crash recovery available immediately.

Note that this refers to "high availability" configurations, where only one gateway is active at any given moment. This is different from "load sharing" configurations where more than one gateway is active at the same time. For load sharing configurations, please see Section 10.2 for security considerations.

## 7. Alternative Solutions

### 7.1. Initiating a new IKE SA

Instead of sending a QCD token, we could have the rebooted implementation start an Initial exchange with the peer, including the INITIAL\_CONTACT notification. This would have the same effect, instructing the peer to erase the old IKE SA, as well as establishing a new IKE SA with fewer rounds.

The disadvantage here, is that in IKEv2 an authentication exchange MUST have a piggy-backed Child SA set up. Since our use case is such that the rebooted implementation does not have traffic flowing to the peer, there are no good selectors for such a Child SA.

Additionally, when authentication is asymmetric, such as when EAP is used, it is not possible for the rebooted implementation to initiate IKE.

### 7.2. SIR

Another proposal that was considered for this work item is the SIR extension, which is described in [recovery]. Under that proposal, the non-rebooted peer sends a non-protected query to the possibly rebooted peer, asking whether the IKE SA exists. The peer replies with either a positive or negative response, and the absence of a positive response, along with the existence of a negative response is taken as proof that the IKE SA has really been lost.

The working group preferred the QCD proposal to this one.

### 7.3. Birth Certificates

Birth Certificates is a method of crash detection that has never been formally defined. Bill Sommerfeld suggested this idea in a mail to the IPsec mailing list on August 7, 2000, in a thread discussing methods of crash detection:

If we have the system sign a "birth certificate" when it reboots (including a reboot time or boot sequence number), we could include that with a "bad spi" ICMP error and in the negotiation of the IKE SA.

XML2PDFRFC-ENDARTWORK

We believe that this method would have some problems. First, it requires Alice to store the certificate, so as to be able to compare the public keys. That requires more storage than does a QCD token. Additionally, the public-key operations needed to verify the self-signed certificates are more expensive for Alice.

We believe that a symmetric-key operation such as proposed here is more light-weight and simple than that implied by the Birth Certificate idea.

#### 7.4. Reducing Liveness Check Length

Some have suggested that the RFC 4306 procedure described in Section 2 can be tweaked by requiring fewer retransmissions over a shorter period of time for cases of liveness check started because of an `INVALID_SPI` or `INVALID_IKE_SPI` notification.

We believe that the default retransmission policy should represent a good balance between the need for a timely discovery of a dead peer, and a low probability of false detection. We expect the policy to be set to take the shortest time such that this probability achieves a certain target. Therefore, reducing elapsed time and retransmission count will create an unacceptably high probability of false detection, and this can be triggered by a single `INVALID_IKE_SPI` notification.

Additionally, even if the retransmission policy is reduced to, say, one minute, it is still a very noticeable delay from a human perspective, from the time that the gateway has come up until the tunnels are active, or from the time the backup gateway has taken over until the tunnels are active.

#### 8. Interaction with Session Resumption

Session Resumption, specified in [RFC5723] proposes to make setting up a new IKE SA consume less computing resources. This is particularly useful in the case of a remote access gateway that has many tunnels. A failure of such a gateway would require all these many remote access clients to establish an IKE SA either with the rebooted gateway or with a backup gateway. This tunnel re-

establishment should occur within a short period of time, creating a burden on the remote access gateway. Session Resumption addresses this problem by having the clients store an encrypted derivative of the IKE SA for quick re-establishment.

What Session Resumption does not help, is the problem of detecting that the peer gateway has failed. A failed gateway may go undetected for as long as the lifetime of a child SA, because IPsec does not have packet acknowledgement, and applications cannot signal the IPsec layer that the tunnel "does not work". Before establishing a new IKE SA using Session Resumption, a client should ascertain that the gateway has indeed failed. This could be done using either a liveness check (as in RFC 4306) or using the QCD tokens described in this document.

A remote access client conforming to both specifications will store QCD tokens, as well as the Session Resumption ticket, if provided by the gateway. A remote access gateway conforming to both specifications will generate a QCD token for the client. When the gateway reboots, the client will discover this in either of two ways:

1. The client does regular liveness checks, or else the time for some other IKE exchange has come. Since the gateway is still down, the IKE exchange times out after several minutes. In this case QCD does not help.
2. Either the primary gateway or a backup gateway (see Section 6) is ready and sends a QCD token to the client. In that case the client will quickly re-establish the IPsec tunnel, either with the rebooted primary gateway or the backup gateway as described in this document.

The full combined protocol looks like this:

```

      Initiator                      Responder
      -----                      -
HDR, SAi1, KEi, Ni  -->
                                <--  HDR, SAR1, KEr, Nr, [CERTREQ]

HDR, SK {IDi, [CERT,]
[CERTREQ,] [IDr,]
AUTH, N(QCD_TOKEN)
SAi2, TSi, TSr,
N(TICKET_REQUEST)}  -->
                                <--  HDR, SK {IDr, [CERT,] AUTH,
                                N(QCD_TOKEN), SAR2, TSi, TSr,
                                N(TICKET_LT_OPAQUE) }

      ---- Reboot ----

HDR, {}                -->
                                <--  HDR, N(QCD_TOKEN)

HDR, [N(COOKIE),]
Ni, N(TICKET_OPAQUE)
[,N+]                  -->
                                <--  HDR, Nr [,N+]

```

XML2PDFRFC-ENDARTWORK

## 9. Operational Considerations

### 9.1. Who should implement this specification

Throughout this document, we have referred to reboot time alternately as the time that the implementation crashes and the time when it is ready to process IPsec packets and IKE exchanges. Depending on the hardware and software platforms and the cause of the reboot, rebooting may take anywhere from a few seconds to several minutes. If the implementation is down for a long time, the benefit of this protocol extension is reduced. For this reason critical systems should implement backup gateways as described in Section 6.

Implementing the "token maker" side of QCD makes sense for IKE implementation where protected connections originate from the peer, such as inter-domain VPNs and remote access gateways. Implementing the "token taker" side of QCD makes sense for IKE implementations where protected connections originate, such as inter-domain VPNs and remote access clients.



To clarify the requirements:

- o A remote-access client **MUST** be a token taker and **MAY** be a token maker.
- o A remote-access gateway **MAY** be a token taker and **MUST** be a token maker.
- o An inter-domain VPN gateway **MUST** be both token maker and token taker.

In order to limit the effects of DoS attacks, a token taker **SHOULD** limit the rate of QCD\_TOKENs verified from a particular source.

If excessive amounts of IKE requests protected with unknown IKE SPIs arrive at a token maker, the IKE module **SHOULD** revert to the behavior described in section 2.21 of [IKEv2bis] and either send an INVALID\_IKE\_SPI notification, or ignore it entirely.

### 9.2. Response to unknown child SPI

After a reboot, it is more likely that an implementation receives IPsec packets than IKE packets. In that case, the rebooted implementation will send an INVALID\_SPI notification, triggering a liveness check. The token will only be sent in a response to the liveness check, thus requiring an extra round-trip.

To avoid this, an implementation that has access to enough non-volatile storage **MAY** store a mapping of child SPIs to owning IKE SPIs, or to generated tokens. If such a mapping is available and persistent across reboots, the rebooted implementation **SHOULD** respond to the IPsec packet with an INVALID\_SPI notification, along with the appropriate QCD-Token notifications. A token taker **SHOULD** verify the QCD token that arrives with an INVALID\_SPI notification the same as if it arrived with the IKE SPIs of the parent IKE SA.

However, a persistent storage module might not be updated in a timely manner, and could be populated with tokens relating to IKE SPIs that have already been rekeyed. A token taker **MUST NOT** take an invalid QCD Token sent along with an INVALID\_SPI notification as evidence that the peer is either malfunctioning or attacking, but it **SHOULD** limit the rate at which such notifications are processed.

### 9.3. Using Tokens that Depend on IP Addresses

This section describes the rationale for token generation methods such as the one described in Section 5.2. Note that this section merely provides a possible rationale, and does not specify or recommend any kind of configuration.

Some configurations of security gateway use a load-sharing cluster of

hosts, all sharing the same IP addresses, where the SAs (IKE and child) are not synchronized between the cluster members. In such a configuration, a single member does not know about all the IKE SAs that are active for the configuration. A load balancer (usually a networking switch) sends IKE and IPsec packets to the several members based on source IP address.

In such a configuration, an attacker can send a forged protected IKE packet with the IKE SPIs of an existing IKE SA, but from a different IP address. This packet will likely be processed by a different cluster member from the one that owns the IKE SA. Since no IKE SA state is stored on this member, it will send a QCD token to the attacker. If the QCD token does not depend on IP address, this token can immediately be used to tell the token taker to tear down the IKE SA using an unprotected QCD\_TOKEN notification.

To thwart this possible attack, such configurations should use a method that considers the taker's IP address, such as the method described in Section 5.2.

## 10. Security Considerations

### 10.1. QCD Token Generation and Handling

Tokens MUST be hard to guess. This is critical, because if an attacker can guess the token associated with an IKE SA, she can tear down the IKE SA and associated tunnels at will. When the token is delivered in the IKE\_AUTH exchange, it is encrypted. When it is sent again in an unprotected notification, it is not, but that is the last time this token is ever used.

An aggregation of some tokens generated by one maker together with the related IKE SPIs MUST NOT give an attacker the ability to guess other tokens. Specifically, if one taker does not properly secure the QCD tokens and an attacker gains access to them, this attacker MUST NOT be able to guess other tokens generated by the same maker. This is the reason that the QCD\_SECRET in Section 5.1 needs to be sufficiently long.

The token taker MUST store the token in a secure manner. No attacker should be able to gain access to a stored token.

The QCD\_SECRET MUST be protected from access by other parties. Anyone gaining access to this value will be able to delete all the IKE SAs for this token maker.

The QCD token is sent by the rebooted peer in an unprotected message.

A message like that is subject to modification, deletion and replay by an attacker. However, these attacks will not compromise the security of either side. Modification is meaningless because a modified token is simply an invalid token. Deletion will only cause the protocol not to work, resulting in a delay in tunnel re-establishment as described in Section 2. Replay is also meaningless, because the IKE SA has been deleted after the first transmission.

### 10.2. QCD Token Transmission

A token maker **MUST NOT** send a QCD token in an unprotected message for an existing IKE SA. This implies that a conforming QCD token maker **MUST** be able to tell whether a particular pair of IKE SPIs represent a valid IKE SA.

This requirement is obvious and easy in the case of a single gateway. However, some implementations use a load balancer to divide the load between several physical gateways. It **MUST NOT** be possible even in such a configuration to trick one gateway into sending a QCD token for an IKE SA which is valid on another gateway.

This document does not specify how a load sharing configuration of IPsec gateways would work, but in order to support this specification, all members **MUST** be able to tell whether a particular IKE SA is active anywhere in the cluster. One way to do it is to synchronize a list of active IKE SPIs among all the cluster members.

### 10.3. QCD Token Enumeration

An attacker may try to attack QCD if the generation algorithm described in Section 5.1 is used. The attacker will send several fake IKE requests to the gateway under attack, receiving and recording the QCD Tokens in the responses. This will allow the attacker to create a dictionary of IKE SPIs to QCD Tokens, which can later be used to tear down any IKE SA.

Three factors mitigate this threat:

- o The space of all possible IKE SPI pairs is huge:  $2^{128}$ , so making such a dictionary is impractical. Even if we assume that one implementation always generates predictable IKE SPIs, the space is still at least  $2^{64}$  entries, so making the dictionary is extremely hard.
- o Throttling the amount of QCD\_TOKEN notifications sent out, as discussed in Section 9.1, especially when not soon after a crash will limit the attacker's ability to construct a dictionary.

- o The methods in Section 5.1 and Section 5.2 allow for a periodic change of the QCD\_SECRET. Any such change invalidates the entire dictionary.

## 11. IANA Considerations

IANA is requested to assign a notify message type from the status types range (16406-40959) of the "IKEv2 Notify Message Types" registry with name "QUICK\_CRASH\_DETECTION".

## 12. Acknowledgements

We would like to thank Hannes Tschofenig and Yaron Sheffer for their comments about Session Resumption.

Frederic D'etienne and Pratima Sethi contributed the ideas in Section 9.3 and Section 5.2.

Others who have contrinuted valuable comments are, in alphabetical order, Lakshminath Dondeti, Scott C Moonen and Dave Wierbowski.

## 13. Change Log

This section lists all changes in this document

NOTE TO RFC EDITOR : Please remove this section in the final RFC

### 13.1. Changes from draft-nir-ike-qcd-07

- o First WG version.
- o Addressed Scott C Moonen's concern about collisions of QCD tokens.
- o Updated references to point to IKEv2bis instead of RFC 4306 and 4718. Also converted draft reference for resumption to RFC 5723.
- o Added Dave Wiebrowski as author, and removed Pratima and Frederic.

### 13.2. Changes from draft-nir-ike-qcd-03 and -04

Mostly editorial changes and cleaning up.

### 13.3. Changes from draft-nir-ike-qcd-02

- o Described QCD token enumeration, following a question by Lakshminath Dondeti.

- o Added the ability to replace the QCD token for an existing IKE SA.
- o Added tokens dependant on peer IP address and their interaction with MOBIKE.

#### 13.4. Changes from draft-nir-ike-qcd-01

- o Removed stateless method.
- o Added discussion of rekeying and resumption.
- o Added discussion of non-synchronized load-balanced clusters of gateways in the security considerations.
- o Other wording fixes.

#### 13.5. Changes from draft-nir-ike-qcd-00

- o Merged proposal with draft-detienne-ikev2-recovery
- o Changed the protocol so that the rebooted peer generates the token. This has the effect, that the need for persistent storage is eliminated.
- o Added discussion of birth certificates.

#### 13.6. Changes from draft-nir-qcr-00

- o Changed name to reflect that this relates to IKE. Also changed from quick crash recovery to quick crash detection to avoid confusion with IFARE.
- o Added more operational considerations.
- o Added interaction with IFARE.
- o Added discussion of backup gateways.

## 14. References

### 14.1. Normative References

#### [IKEv2bis]

Kaufman, C., Hoffman, P., Nir, Y., and P. Eronen, "Internet Key Exchange Protocol: IKEv2", draft-ietf-ipsecme-ikev2bis-11 (work in progress), May 2010.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC4555] Eronen, P., "IKEv2 Mobility and Multihoming Protocol (MOBIKE)", RFC 4555, June 2006.

## 14.2. Informative References

[RFC5723] Sheffer, Y. and H. Tschofenig, "IKEv2 Session Resumption", RFC 5723, January 2010.

[cluster] Nir, Y., Ed., "IPsec Cluster Problem Statement", draft-ietf-ipsecme-ipsec-ha (work in progress), July 2010.

[recovery] Detienne, F., Sethi, P., and Y. Nir, "Safe IKE Recovery", draft-detienne-ikev2-recovery (work in progress), January 2010.

## Authors' Addresses

Yoav Nir (editor)  
Check Point Software Technologies Ltd.  
5 Hasolelim st.  
Tel Aviv 67897  
Israel

Email: [ynir@checkpoint.com](mailto:ynir@checkpoint.com)

David Wierbowski  
International Business Machines  
1701 North Street  
Endicott, New York 13760  
United States

Email: [wierbows@us.ibm.com](mailto:wierbows@us.ibm.com)