

Network Working Group
Internet-Draft
Intended status: Informational
Expires: December 25, 2016

S. Smyshlyayev, Ed.
E. Alekseev
I. Oshkin
V. Popov
CRYPTO-PRO
June 23, 2016

The Security Evaluated Standardized Password Authenticated Key Exchange
(SESPAKE) Protocol
draft-smyshlyayev-sespake-08

Abstract

This document specifies the Security Evaluated Standardized Password Authenticated Key Exchange (SESPAKE) protocol. The SESPAGE protocol provides password authenticated key exchange for usage in the systems for protection of sensitive information. The security proofs of the protocol was made for the case of an active adversary in the channel, including MitM attacks and attacks based on the impersonation of one of the subjects.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 25, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents
(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Conventions used in this document	2
3. Notations	2
4. Protocol description	4
4.1. Protocol parameters	4
4.2. Initial values of the protocol counters	6
4.3. Protocol steps	6
5. Construction of points Q_1,...,Q_N	9
6. Acknowledgments	9
7. Security Considerations	9
8. Normative References	10
Appendix A. Test examples for GOST-based protocol implementation	11
A.1. Examples of points	11
A.2. Test examples	17
Authors' Addresses	28

1. Introduction

The current document contains the description of the password authenticated key exchange protocol SESPKE (security evaluated standardized password authenticated key exchange) for usage in the systems for protection of sensitive information. The protocol is intended to use for establishment of keys that are then used for organization of secure channel for protection of sensitive information. The security proofs of the protocol was made for the case of an active adversary in the channel, including MitM attacks and attacks based on the impersonation of one of the subjects.

2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

3. Notations

This document uses the following parameters of elliptic curves in accordance with [RFC6090]:

E an elliptic curve defined over a finite prime field GF(p), where $p > 3$;

p the characteristic of the underlying prime field;

a, b the coefficients of the equation of the elliptic curve in the canonical form;

m the elliptic curve group order;

q the elliptic curve subgroup order;

P generator of the subgroup of order q;

X, Y the coordinates of the elliptic curve point in the canonical form;

O zero point (point of infinity) of the elliptic curve.

This memo uses the following functions:

HASH the underlying hash function;

HMAC the function for calculating a message authentication code, based on a HASH function in accordance with [RFC2104];

$F(PW, salt, n)$ the value of the function PBKDF2($PW, salt, n, len$), where PBKDF2($PW, salt, n, len$) is calculated according to [RFC2898] The parameter len is considered equal to minimal integer that is a multiple of 8 and satisfies the following condition:
 $len \geq \text{floor}(\log_2(q))$.

This document uses the following terms and definitions for the sets and operations on the elements of these sets

B_n the set of byte strings of size n , $n \geq 0$, for $n = 0$ the B_n set consists of a single empty string of size 0; if b is an element of B_n , then $b = (b_1, \dots, b_n)$, where b_1, \dots, b_n are elements of $\{0, \dots, 255\}$;

$\text{int}(w')$ if the byte string $w' = (w_1, \dots, w_t)$ is in B_t , then $\text{int}(w')$ is an integer $w = 256^{(t-1)}w_t + \dots + 256^{(0)}w_1$;

$\text{INT}(w')$ if the byte string $w' = (w_1, \dots, w_t)$ is in B_t , then $\text{INT}(w')$ is an integer $W = 256^{(t-1)}w_1 + \dots + 256^{(0)}w_t$;

|| concatenation of byte strings A and C, i.e., if A in B_{n1} , C in B_{n2} , $A = (a_1, a_2, \dots, a_{n1})$ and $C = (c_1, c_2, \dots, c_{n2})$, then $A||C = (a_1, a_2, \dots, a_{n1}, c_1, c_2, \dots, c_{n2})$ is an element of $B_{(n1+n2)}$;

Byte representation of a point (X, Y) . If (X, Y) is an elliptic curve point then the byte representation of (X, Y) is a concatenation of the coordinates of this point $X||Y$; the length of the byte representations of the coordinates X and Y is equal to the minimum possible length of the byte representation of the subgroup generator p.

4. Protocol description

The protocol is used by subjects A and B that are commencing key establishment with password-based authentication.

4.1. Protocol parameters

Various elliptic curves can be used in the protocol. For each elliptic curve supported by clients the following values must be defined:

- o the curve identifier ID_ALG, that is a byte string of arbitrary length;
- o the point P, that is a generator point of the subgroup of order q of the curve;
- o the set of distinct curve points $\{Q_1, Q_2, \dots, Q_N\}$ of order q, where the total number of points N is defined for protocol instance.

The method of generation of the points $\{P, Q_1, Q_2, \dots, Q_N\}$ is described in Section 5.

The protocol parameters that are used by subject A are the following:

1. The secret password value PW, which is a byte string that is uniformly randomly chosen from a subset of cardinality 10^{10} or greater of the set B_k , where $k \geq 6$ is password length.
2. The list of curve identifiers supported by A.
3. Sets of points $\{Q_1, Q_2, \dots, Q_N\}$, corresponding to curves supported by A.

4. The C_{1^A} counter, that tracks the total number of unsuccessful authentication trials in a row, and a value of $CLim_1$ that stores the maximum possible number of such events.
5. The C_{2^A} counter, that tracks the total number of unsuccessful authentication events during the period of usage of the specific PW, and a value of $CLim_2$ that stores the maximum possible number of such events.
6. The C_{3^A} counter, that tracks the total number of authentication events (successful and unsuccessful) during the period of usage of the specific PW, and a value of $CLim_3$ that stores the maximum possible number of such events.
7. The unique identifier ID_A of the subject A (OPTIONAL), which is a byte string of an arbitrary length.

The protocol parameters that are used by subject B are the following:

1. The values ind and $salt$, where ind is in $\{1, \dots, N\}$, $salt$ is in $\{1, \dots, 2^{128}-1\}$.
2. The point Q_{PW} , satisfying the following equation:

$$Q_{PW} = \text{int}(F(PW, salt, 2000)) * Q_{ind}.$$

It is possible that the point Q_{PW} is not stored and is calculated using PW in the beginning of the protocol. In that case B has to store PW and points Q_1, Q_2, \dots, Q_N .

3. The ID_{ALG} identifier of the elliptic curve used in the protocol.
4. The C_{1^B} counter, that tracks the total number of unsuccessful authentication trials in a row, and a value of $CLim_1$ that stores the maximum possible number of such events.
5. The C_{2^B} counter, that tracks the total number of unsuccessful authentication events during the period of usage of the specific PW, and a value of $CLim_2$ that stores the maximum possible number of such events.
6. The C_{3^B} counter, that tracks the total number of authentication events (successful and unsuccessful) during the period of usage of the specific PW, and a value of $CLim_3$ that stores the maximum possible number of such events.
7. The unique identifier ID_B of the subject B (OPTIONAL), which is a byte string of an arbitrary length.

4.2. Initial values of the protocol counters

After the setup of a new password value PW the values of the counters must be assigned as follows:

- o $C_1^A = C_1^B = CLim_1$, where $CLim_1$ is in $\{3, \dots, 5\}$;
- o $C_2^A = C_2^B = CLim_2$, where $CLim_2$ is in $\{7, \dots, 20\}$;
- o $C_3^A = C_3^B = CLim_3$, where $CLim_3$ is in $\{10^3, 10^{3+1}, \dots, 10^5\}$.

4.3. Protocol steps

The described protocol consists of the following steps:

1. If any of the counters C_1^A , C_2^A , C_3^A is equal to 0, A finishes the protocol with an error that informs of exceeding the number of trials that is controlled by the corresponding counter.
2. A decrements each of the counters C_1^A , C_2^A , C_3^A by 1, requests open authentication information from B and sends the ID_A identifier.
3. If any of the counters C_1^B , C_2^B , C_3^B is equal to 0, B finishes the protocol with an error that informs of exceeding the number of trials that is controlled by the corresponding counter.
4. B decrements each of the counters C_1^B , C_2^B , C_3^B by 1.
5. B sends the values of ind, salt and the ID_ALG identifier to A. B also can OPTIONALY send the ID_B identifier to A. All following calculations are done by B in the elliptic curve group defined by the ID_ALG identifier.
6. A sets the curve defined by the received ID_ALG identifier as the used elliptic curve. All following calculations are done by A in this elliptic curve group.
7. A calculates the point $Q_{PW^A} = \text{int}(F(PW, \text{salt}, 2000)) * Q_{ind}$.
8. A chooses randomly (according to the uniform distribution) the value alpha, alpha is in $\{1, \dots, q-1\}$, and assigns $z_A = 0$.
9. A sends the value $u_1 = \text{alpha} * P - Q_{PW^A}$ to B.

10. After receiving u_1 , B checks that u_1 is in E. If it is not, B finishes with an error, considering the authentication process unsuccessful.
11. B calculates $Q_B = u_1 + Q_{PW}$, assigns $z_B = 0$ and chooses randomly (according to the uniform distribution) the value betta, betta is in $\{1, \dots, q-1\}$.
12. If $m/q*Q_B = 0$, B assigns $Q_B = \text{betta}^P$ and $z_B = 1$.
13. B calculates $K_B = \text{HASH}((m/q*\text{betta}^{(\text{mod } q)})*Q_B)$, where the input of a hash function is a little-endian representation of the obtained point (x-coordinate first, then y-coordinate).
14. B sends the value $u_2 = \text{betta}^P + Q_{PW}$ to A.
15. After receiving u_2 , A checks that u_2 is in E. If it is not, A finishes with an error, considering the authentication process unsuccessful.
16. A calculates $Q_A = u_2 - Q_{PW}^A$.
17. If $m/q*Q_A = 0$, then A assigns $Q_A = \alpha^P$ and $z_A = 1$.
18. A calculates $K_A = \text{HASH}((m/q*\alpha^{(\text{mod } q)})*Q_A)$, where the input of a hash function is a little-endian representation of the obtained point (x-coordinate first, then y-coordinate).
19. A calculates $\text{MAC}_A = \text{HMAC}(K_A, 0x01 || ID_A || \text{ind} || \text{salt} || u_1 || u_2 || \text{DATA}_A)$, where DATA_A is an OPTIONAL string that is authenticated with MAC_A (if it is not used, then DATA_A is considered to be of zero length).
20. A sends $(\text{DATA}_A || \text{MAC}_A)$ to B.
21. B checks that the values MAC_A and $\text{HMAC}(K_B, 0x01 || ID_A || \text{ind} || \text{salt} || u_1 || u_2 || \text{DATA}_A)$ are equal. If they are not, it finishes with an error, considering the authentication process unsuccessful.
22. If $z_B = 1$, B finishes, considering the authentication process unsuccessful.
23. B sets the value of C_1^B to CLim_1 and increases C_2^B by 1.
24. B calculates $\text{MAC}_B = \text{HMAC}(K_B, 0x02 || ID_B || \text{ind} || \text{salt} || u_1 || u_2 || \text{DATA}_A || \text{DATA}_B)$, where DATA_B is an OPTIONAL

string that is authenticated with MAC_B (if it is not used, then DATA_B is considered to be of zero length).

25. B sends (DATA_B || MAC_B) to A.
26. A checks that the values MAC_B and HMAC (K_A, 0x02 || ID_B || ind || salt || u_1 || u_2 || DATA_A || DATA_B) are equal. If they are not, it finishes with an error, considering the authentication process unsuccessful.
27. If z_A = 1, A finishes, considering the authentication process unsuccessful.
28. A sets the value of C_1^A to CLim_1 and increases C_2^A by 1.

After the successful finish of the procedure the subjects A and B are mutually authenticated and each subject has an explicitly authenticated value of K = K_A = K_B.

Note:

1. In the case where the interaction process can be initiated by any subject (client or server) the ID_A and ID_B options MUST be used and the receiver MUST check that the identifier he had received is not equal to his own, otherwise, it finishes the protocol. If an optional parameter ID_A (or ID_B) is not used in the protocol, it SHOULD be considered equal to a fixed byte string (zero-length string is allowed) defined by a specific implementation.
2. The ind, ID_A, ID_B and salt parameters can be agreed in advance. If some parameter is agreed in advance, it is possible not to send it during a corresponding step. Nevertheless, all parameters MUST be used as corresponding inputs to HMAC function during stages 19, 21, 24 and 26.
3. The ID_ALG parameter can be fixed or agreed in advance.
4. Continuation of protocol interaction in case of any of the counters C_1^A, C_1^B being equal to zero MAY be done without changing password. In this case these counters can be used for protection against denial-of-service attacks. For example, continuation of interaction can be allowed after a certain delay.
5. Continuation of protocol interaction in case of any of the counters C_2^A, C_3^A, C_2^B, C_3^B being equal to zero MUST be done only after changing password.

5. Construction of points Q_1, \dots, Q_N

This section provides an example of possible algorithm for generation of each point Q_i in the set $\{Q_1, \dots, Q_N\}$ that corresponds to the given elliptic curve E .

The algorithm is based on choosing points with coordinates with a known preimages of a cryptographic hash function H , which is the GOST R 34.11-2012 hash function (see [RFC6986]) with 256-bit output, if $2^{254} < q < 2^{256}$, and the GOST R 34.11-2012 hash function (see [RFC6986]) with 512-bit output , if $2^{508} < q < 2^{512}$.

The algorithm consists of the following steps:

1. Choose an arbitrary SEED value with length of 32 bytes or more.
2. Calculate $X = \text{INT}(H(\text{SEED})) \bmod p$.
3. Check that the value of $X^3 + aX + b$ is a quadratic residue in the field F_p . If it is not, return to Step 1.
4. Choose the value of Y arbitrarily from the set $\{+\sqrt{R}, -\sqrt{R}\}$, where $R = X^3 + aX + b$. Here \sqrt{R} is an element of F_p , for which $(\sqrt{R})^2 = R \bmod p$.
5. Check that for point $Q = (X, Y)$ the following relations hold: $Q \neq O$ and $q*Q = O$. If they do not, return to Step 1.

With the defined algorithm for any elliptic curve E point sets $\{Q_1, \dots, Q_N\}$ are constructed. Constructed points in one set MUST have distinct x-coordinates.

Note: The knowledge of hash function preimage prevents knowledge of the multiplicity of any point related to generator point P . It is of primary importance, because such a knowledge could be used to implement an attack against protocol with exhaustive search of password.

6. Acknowledgments

We thank Lolita Sonina, Georgiy Borodin, Sergey Agafin and Ekaterina Smyshlyayeva for their careful readings and useful comments.

7. Security Considerations

Any cryptographic algorithms, particularly HASH function and HMAC function, that are used in the SESPKE protocol MUST be carefully

designed and MUST be able to withstand all known types of cryptanalytic attack.

It is RECOMMENDED that the HASH function satisfies the following condition:

$\text{hashlen} \leq \log_2(q) + 4$, where hashlen is the lengths of the HASH function output.

The output length of hash functions that are used in the SESPAKE protocol is RECOMMENDED to be greater or equal to 256 bits.

The points Q_1, Q_2, \dots, Q_3 and P must be chosen in such a way that they are provable pseudorandomness. As a practical matter, this means that the algorithm for generation of each point Q_i in the set $\{Q_1, \dots, Q_N\}$ (see Section 5) ensures that multiplicity of any point under any other point is unknown.

8. Normative References

[GOST3410-2012]

Federal Agency on Technical Regulating and Metrology (In Russian), "Information technology. Cryptographic data security. Signature and verification processes of [electronic] digital signature", GOST R 34.10-2012, 2012.

[GOST3411-2012]

Federal Agency on Technical Regulating and Metrology (In Russian), "Information technology. Cryptographic Data Security. Hashing function", GOST R 34.11-2012, 2012.

[RFC2104] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", RFC 2104, DOI 10.17487/RFC2104, February 1997, <<http://www.rfc-editor.org/info/rfc2104>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

[RFC2898] Kaliski, B., "PKCS #5: Password-Based Cryptography Specification Version 2.0", RFC 2898, DOI 10.17487/RFC2898, September 2000, <<http://www.rfc-editor.org/info/rfc2898>>.

- [RFC6090] McGrew, D., Igoe, K., and M. Salter, "Fundamental Elliptic Curve Cryptography Algorithms", RFC 6090, DOI 10.17487/RFC6090, February 2011, <<http://www.rfc-editor.org/info/rfc6090>>.
- [RFC6986] Dolmatov, V., Ed. and A. Degtyarev, "GOST R 34.11-2012: Hash Function", RFC 6986, DOI 10.17487/RFC6986, August 2013, <<http://www.rfc-editor.org/info/rfc6986>>.
- [RFC7091] Dolmatov, V., Ed. and A. Degtyarev, "GOST R 34.10-2012: Digital Signature Algorithm", RFC 7091, DOI 10.17487/RFC7091, December 2013, <<http://www.rfc-editor.org/info/rfc7091>>.
- [RFC7836] Smyshlyayev, S., Ed., Alekseev, E., Oshkin, I., Popov, V., Leontiev, S., Podobaev, V., and D. Belyavsky, "Guidelines on the Cryptographic Algorithms to Accompany the Usage of Standards GOST R 34.10-2012 and GOST R 34.11-2012", RFC 7836, DOI 10.17487/RFC7836, March 2016, <<http://www.rfc-editor.org/info/rfc7836>>.

Appendix A. Test examples for GOST-based protocol implementation

The following test examples are made for the protocol implementation that is based on the Russian national standards GOST R 34.10-2012 [GOST3410-2012] and GOST R 34.11-2012 [GOST3411-2012]. The English versions of these standards can be found in [RFC7091] and [RFC6986].

A.1. Examples of points

There are three points (Q_1 , Q_2 , Q_3) for each of the elliptic curves below. These points were constructed using the method described in Section 5, where the GOST R 34.11-2012 hash function (see [RFC6986]) with 256-bit output is used if $2^{254} < q < 2^{256}$ and the GOST R 34.11-2012 hash function (see [RFC6986]) with 512-bit output is used if $2^{508} < q < 2^{512}$.

The same method should be used for constructing, if necessary, additional points. Each of the points complies with the GOST R 34.10-2012 [GOST3410-2012] standard and is represented by a pair of (X, Y) coordinates in the canonical form and by a pair of (U, V) coordinates in the twisted Edwards form in accordance with the document [RFC7836] for the curves that have the equivalent representation in this form. There is a SEED value for each point, by which it was generated.

A.1.1 Curve id-GostR3410-2001-CryptoPro-A-ParamSet Point Q_1

X= 0xa33ce065b0c23e1d3d026a206f8a1f8747ed1cd92a665bf85198cdb10ac90a5c
Y= 0xb00d0dc0733883f05de9f55fd711f55998f5508cc40bead80c913b4d5b533667
SEED:

```
f8 18 95 b4 13 69 d9 08 9e 3d 3c 56 e8 70 ba 5e
9d 55 5e 20 eb d9 c7 22 66 10 6d 79 c2 83 48 b8
ce 63 70 52 9a 82 9f 18 a4 d3 e3 fd 7b f2 dd 73
b1 1b bc d4 10 9d 27 c9 a3 d4 bd 3a 42 cc 26 ae
43 5b 52 f5 89 a4 c3 b7 61 c0 1b a2 88 b7 e0 8d
f9 4e 22 40 29 f3 aa 96 11 5c 43 f5 eb 87 99 70
```

Point Q_2

X= 0x4ce9c2bcf17212b9efcab65c3c815c0ff96d7461c957634dbfd1fe7c9a324d27
Y= 0xf7500d7adea2c2b4a16d838a8faa02b46639eb881f124d0f2506efca0e24289d
SEED:

```
fd 99 6d bc c7 2e 49 a4 37 e7 49 a8 85 ad de 28
4b 58 64 bd 3b 7e 60 fc b5 2f c8 36 0e 0a bf 98
fd 35 7a 3f 98 c5 f6 20 c8 68 3d b2 ca b9 27 b6
13 f2 91 a1 52 45 c0 65 71 dc 62 b0 4f 2e e5 76
56 a9 fa 51 12 23 5d 0b 80 67 59 af e2 33 b1 09
6a 94 84 91 45 f2 18 50 65 b7 9b 86 ab 68 8a 39
```

Point Q_3

X= 0x31fb8e5070b1e0f52f047f40477c38c6020fd8da9f685791f9237cc47bd89324
Y= 0x8ba1184a4e296dc5c5873639747339ecc71b7fa44d31cc8e35b6615a4f797dd7
SEED:

```
29 0c 12 66 47 91 2e de 11 cc 43 78 0c f8 87 d4
7d a1 63 bc fb 91 1d 92 86 2a ae 4f 53 a6 80 70
08 c1 ec 0c 8f e7 2e 0a a0 81 df a3 32 7c 86 ad
5f 24 da 28 a7 1d 07 f5 fd b7 61 31 a1 fb 04 d5
b2 31 c7 7f ca 26 d3 a6 42 99 9e 3b 10 74 b5 a7
b3 54 2f 03 b0 39 63 2a 6b 44 56 36 fb 52 8d 58
```

A.1.2 Curve id-GostR3410-2001-CryptoPro-B-ParamSet

Point Q_1

X= 0x0ad754474a915d9d706c6b8dc879858a1cb85cc8f6c148fc3120825393ecd394
Y= 0x68c33b6d0343cf72cb19666ffd487fa94294dc677b28c8e27ec36068ff85ed83
SEED:

```
78 1d 7d 85 ff 04 12 b9 92 a7 6e 65 37 dd 83 81
9b 81 2f fa bf e8 92 3c d0 12 fe dc 00 c4 96 69
f6 52 44 4d 38 9a f2 b2 6f 57 b5 3e 2d 0f 81 2e
db 2c f3 d6 a7 18 42 52 32 da 47 18 75 1e ec ef
8f 2b c5 03 17 fb 49 6f 02 05 d7 99 bc 3c 34 87
12 f5 1b d3 ef aa 7f f5 ba c2 52 07 80 46 34 77
```

Point Q_2

X= 0x1cd96e72fdf1ce6b544dec12d0d7bcb9f6ba65bba3d9f7af732bcb133c1b6437
Y= 0x34ab5b63c286a2b885ca443ac875a8f9ec0c2f148f1622bc64c83b80e6e3d31f
SEED:

```
62 93 40 15 63 0c 9a 09 ce 76 32 6c fd 1c 04 36
ee 08 bc 92 b9 c0 3a d9 63 c6 db 00 18 12 12 fa
e0 1a 46 38 8b b6 81 df ae 4f 64 3e cc 0c 93 8c
```

```
e4 10 36 2f d9 6d 5c fd 99 f3 9c 13 fd 30 52 a1
3e 8b 35 8b ed 1c 31 b0 39 9c 03 dc 5a 94 2b 41
f8 ff 9d 62 41 bd eb 9d bf cf 54 b6 c8 cc d1 06
```

Point Q_3

```
X= 0x18dda7154e5abef001dc9943554439cb44b9e26256def176849da5f09b5f690d
```

```
Y= 0x3ef584be59673d1751b2fd6e3fdc619e3d756c0d355595b3a62196de048ece44
```

SEED:

```
33 17 39 c1 38 82 98 88 14 68 83 c6 97 14 86 8c
d0 d2 1a 28 41 51 99 a9 33 40 15 0b 30 88 35 01
4a 41 42 f8 d8 9a a6 bd e1 a6 81 23 94 19 e8 a0
ef 3d 36 02 ef ff 38 e6 10 4b 11 2f 7b b5 50 42
5a 7b 39 a6 00 53 1a 92 fc cc 2b 0d 95 dd ea 95
42 d4 27 6f a8 0f ae 45 b2 d6 f4 38 c1 52 17 5d
```

A.1.3 Curve id-GostR3410-2001-CryptoPro-C-ParamSet

Point Q_1

```
X= 0x339f791f62938871f241c1c89643619aa8b2c7d7706ce69be01fddff3f840003
```

```
Y= 0x31d6d9264cc6f8fe09bf7aa48910b4ad5ddf74a2ef4699b76de09ffed295f11
```

SEED:

```
0e 29 35 9d 45 dd a3 b4 57 9b 17 e8 87 d9 9e 63
b9 d6 04 e3 ac 74 83 11 91 2a 5b d4 86 7b 5d 9c
5d 07 70 64 cd f1 2d 93 f7 f0 2e f0 0a e1 7b 8b
c1 87 50 b3 8f 39 bb 95 68 21 5c 42 e2 4e 8c fe
59 e9 0f a6 05 0b 76 68 a2 94 da 5f 2c 9a 27 28
1f 3a 7e 4e 14 54 10 21 01 6f 2c a2 97 77 94 12
```

Point Q_2

```
X= 0x80f4d03b00b1b9b53f6bb4ffa52be65a6d316de846e27f44cc795bc62d89e23
```

```
Y= 0x38dd712518ddec19b46afccccba97338d89d1292427dc12985d4e848066cd1ab
```

SEED:

```
f5 61 4e 92 8f e5 5c 77 26 37 ab ac 1b 1e 3c dd
2a 37 77 be 25 23 cc 58 9a 79 5a 60 28 db 9e 64
f8 62 73 01 98 3e dd 23 0b eb 07 3e 81 9b cb d9
94 bc bf 7f 9e 5f e1 8f a5 8a ce 9e f2 99 0e 9d
fb ee 1c 64 38 22 33 c3 1b e7 05 9e c2 e9 bb 46
b9 dc 15 19 9d e0 9f cb 65 d5 6d 46 2f 01 21 65
```

Point Q_3

```
X= 0xc8b64c3f0ec7ece81b6232db2e8054666d051ee28254d4b9a4bcb1460ca546b
```

```
Y= 0x88c98b48b22b90d0d3a018da55ca0d05cedd82b6c838bd62aba2b823ce82b28f
```

SEED:

```
8a 1b 29 62 38 f5 c2 e2 9b 4a c0 5b 6d 57 99 88
86 69 a4 1b b9 f6 60 f3 a3 15 26 e5 f4 33 1e ae
80 9a 38 52 f5 44 86 91 71 76 1c ab 77 0a b6 2e
c3 6f d6 4d 3c 31 a3 67 2a 82 25 bf d6 ae c9 95
66 95 b8 87 39 6a 3e bf ef 28 65 16 b9 51 29 1d
65 df 12 7a eb 4c ec f1 6f 08 f5 98 36 0a b9 a0
```

A.1.4 Curve id-tc26-gost-3410-2012-512-paramSetA

Point Q_1

X= 0x301aac1a3b3e9c8a65bc095b541ce1d23728b93818e8b61f963e5d5b13eec0fe

e6b06f8cd481a07bb647b649232e5179b019eef7296a3d9cfab2b66ee8bf0cbf2

Y= 0x191177dd41ce19cc849c3938abf3adaab366e5eb2d22a972b2dcc69283523e89

c9907f1d89ab9d96f473f96815da6e0a47297fcdd8b3adac37d4886f7ad055e0

SEED:

64	1c	90	19	c5	d7	68	91	de	d1	9a	31	28	4e	7c	d3
c6	8b	74	e5	e6	a7	20	b5	2c	fb	45	17	9f	91	b3	f6
3a	0c	b2	5e	3f	91	e3	eb	80	3d	80	4f	79	98	a3	57
f2	e5	dc	5d	84	ab	d6	7d	33	a3	2b	89	66	db	c6	94
96	8f	96	2d	37	9e	33	c0	fd	14	32	dd	02	70	fb	61
1a	88	4c	6d	ae	1b	58	20	24	6e	80	80	5d	cd	a8	66

Point Q_2

X= 0x7edc38f17f88e3105bafb67c419d58fe6a9094dd4dc1a83bcaccc61f020ac447
92eba888457c658ee2d82557b7c6ab6efd61ba0c3327741d09a561a8b860a085

Y= 0x3af1400a7a469058d9ba75e65ea5d3f4d0bdb357fa57eb73fa4900e2dca4da78
b8e5ff35ca70e522610bb1fc76b102c81cc4729f94b12822584f6b6229a57ea1

SEED:

3d	ad	a1	b4	fb	87	3e	13	1e	51	62	60	1f	ee	f1	54
b0	77	e0	71	1b	cf	da	74	a2	20	7e	a3	20	01	c3	f5
79	00	5f	10	9f	c1	83	83	4e	29	46	b3	29	8a	4c	10
0c	69	f4	c6	40	92	3f	ed	af	b2	68	08	0b	6b	1c	07
48	a1	18	29	6e	64	9b	f6	1d	eb	26	27	b4	77	9e	e8
e0	ff	c1	db	48	5d	8b	c1	10	8c	58	b1	af	07	5f	7b

Point Q_3

X= 0x387acfba7bbc5815407474a7c1132a1bded12497243d73ef8133d9810eb21716
95dde2ff15597e159464a1db207b4d1ff98fb989f80c2db13bc8ff5fea16d59

Y= 0x4c816d1ca3e145ac448478fb79a77e1ad2dfc69576685e2f6867ec93fbad8aa4
4111acd104036317095bce467e98f295436199c8ead57f243860d1bde8d88b68

SEED:

7c	8d	a6	91	96	0d	9d	06	65	92	23	08	df	cf	51	71
bd	7c	4b	f8	50	1b	3f	fd	3c	b1	58	3a	30	e1	a7	17
4e	09	e2	5f	1d	19	35	6e	b0	51	66	1c	d0	2a	c1	9e
48	22	38	49	76	0d	43	4e	20	ea	d1	80	73	84	1c	e8
36	a6	8e	f3	24	bb	2d	57	45	32	a5	d4	e6	08	73	fa
d3	8c	32	e8	af	a1	c5	25	8c	ff	3d	52	ca	ac	98	d1

A.1.5 Curve id-tc26-gost-3410-2012-512-paramSetB

Point Q_1

X= 0x488cf12b403e539fde9ee32fc36b6ed52aad9ec34ff478c259159a85e99d3dda
dfd5d73606eceee351e0f780a14c3e9f14e985d9d7ddec93b064fc89b0c843650

Y= 0x7bc73c032edc5f2c74dd7d9da12e1856a061ce344a77253f620592752b1f3a3d
cbbc87eb27ec4ed5e236dfcb03f3972404747e277671e53a9e412e82aaaf6c3f7

SEED:

40	57	8b	1a	c0	bd	53	8d	75	97	2d	49	9b	1c	c6	73
94	c8	f7	d4	76	cd	fe	15	59	02	fa	0f	28	b8	06	e1
81	4c	fb	d0	4d	62	86	0c	4a	ce	c1	0e	88	13	da	2a
d4	fd	7a	13	4d	ba	75	0d	2c	80	f2	68	ba	c1	b4	34
98	ea	fe	10	51	86	60	b7	70	30	f8	64	6f	21	d9	40

```

aa da 62 3e ad 44 3f 93 73 a5 6b c3 15 55 3c bd
Point Q_2
X= 0x175166b97248bda12ec035df2e312a2771d0b16977c9cbc79461ff05e01f719c
    92ae8b53f3b7e3edcacffcc5063b5e9c8de18d0cb87da358350992132173df69
Y= 0x10e2943dc1a18a841ab76ac756fa974948d5a18d071d458a4769c2494fe2a6c5
    966e3c8931e624d87259156aea9317157502698e4a4a489c327b89277cf59b4c
SEED:
26 01 07 1b 3d 3e 6d e7 0e d0 22 ae be 81 be 47
51 77 49 b6 5d 29 d1 07 5c df cb f4 56 a8 77 54
2b e9 91 50 34 06 b3 aa 71 c5 ce 16 b6 5f e9 93
e7 48 99 58 b1 26 81 10 9f 9b e4 30 38 73 77 13
f0 6a 4f 30 05 b2 66 76 9f b8 1b 5f 39 55 52 97
ab 46 6b 5d 2e 19 2d 12 f3 2a b3 18 72 71 52 62

Point Q_3
X= 0x01f4583db894cdebd7c591af848783ee011a20567751ca1561f398a6118ace08
    a4efe1501bda67f39d060270ba660526dc53063c6b40fa5548c9a9e7688f2239
Y= 0x7bc640641d70c8296bd9257c9eebb5b1bd3196a169bac04f7579bf27b5847d4e
    7b4f63748ad81b5469070ed35ad93e5a5258652306f84094eae04a91954536ee
SEED:
bb 9a 63 a5 67 7d 40 7c f3 4d 06 df 96 7d d9 e9
ca 4d 42 eb d6 7d a5 69 a4 9b d8 b1 04 64 2e 20
fb a9 9d 84 2f cb 54 76 61 dc 7a a4 de 72 6f 67
4a 09 85 46 20 04 7c c1 75 2c ab 67 99 8b 5c 8e
6a 88 6d 0a 06 e6 a3 fa e8 19 34 21 1a ec 81 8d
89 03 9e 45 dc a1 85 03 7e c3 49 37 33 ee 3c 2e

A.1.6 Curve id-tc26-gost-3410-2012-256-paramSetA
Point Q_1
X= 0x5161b08a973d521bdde0cbd45b68aa0470e1058dd936e5bd618fd3373770eed9
Y= 0xc1633db551677c62b9c2b69d47e503c0f8ca83b6b3109dece0a5f985d77a83a7
U= 0x9c5ad63ddc3314ac009d879780d6219720bf4573f4fe6b4bf7a0a88860677f9d
V= 0x8ee071a767f3d6f0435eb6100d1a936f984e43d9af0bc91c864a9e65cee025fb
SEED:
c4 7e 5e 42 31 4e dd 8e e9 ac 39 fb c8 da ea c8
e6 5b fd 26 58 27 4e 1f 99 e9 33 e1 1e 5d f2 62
4a e3 97 f1 7e db f9 83 60 f3 ec 2e 8f 6f 2e ff
d4 aa 80 5c 71 d6 ed 5b a1 5b c9 d0 ad d6 38 23
84 c1 55 20 a5 b8 bb bd 7b 23 1f c8 fb 8c 77 71
57 b9 77 25 91 55 3f 17 46 8c 4b b3 64 6f 9f 53

Point Q_2
X= 0xd47abd59dccad35849dec9dc721ffa1e44419ca8686406a9f441e61294b210ed
Y= 0xa78b64220bf3375d08de0ea5e2920cf8f204da6757bf1878ac870fb7e5ca0e8
U= 0xf0195efb6b249eb8018c19376907c787511bf30516a5c27d045fc7ba2af58ed0
V= 0xacae88466127df000b663863bc7bd394eafa6996fcedad11d7834f502a6a2686
SEED:
30 5f d0 bb ce c7 16 49 ac e4 1b 4d ca 07 6c a6
96 a8 8c c6 fd 06 91 a8 79 13 5d e1 90 96 e3 c8

```

```
03 c5 b4 ad 41 68 36 9b e7 b9 ed 81 d6 e2 bd 0c
a2 8e b0 e9 6f 74 2d 50 e2 df b6 a1 86 ae 15 60
96 a3 5a 97 a2 20 fa 6d 0f cf 88 db 6d 86 cd db
19 7c 3a 21 5f 10 cc ea 42 95 ef aa b2 63 95 d5
```

Point Q_3

```
X= 0xe0d610ff42ce21eb308980964ca368963fbe5cb08c277187d22d0c94f4bf0762
Y= 0x82619b88da25b666e07b617ff487be8afdf5af8b092568b493ec44ee0c04b5f
U= 0x723df0719311d095b814ee05ca086e18c410c375a48789dc03c3fe844ed3b7c9
V= 0x160e1b5338337ee0620745206dbe5556a7ff5d19735418a3cc03bf7f2735ce25
```

SEED:

```
22 16 91 c7 21 8d 93 d4 a8 ad 15 e4 72 33 84 90
ca 5c 5e 3b 84 84 57 4e bc df 83 26 68 84 5e f4
09 53 71 79 7a f8 e2 a6 e3 99 93 de 2a 7c 65 f0
37 26 2e cc fa 95 58 9a c6 e8 b1 2d e6 09 af be
f9 2f 12 d0 a3 08 56 9a b3 c0 fa d8 ec 5d 7b 9c
f4 27 1f aa 54 bc bb da 31 61 b7 cd f5 40 d6 b8
```

A.1.7 Curve id-tc26-gost-3410-2012-512-paramSetC

Point Q_1

```
X= 0x5b065ead2e94de0ee2e462de204c93c6b2bf3498ad920393cb60259e1a8ffc7c
    7e7d4defa20ff4282abf70207e4611d532f40db6800e29d2b53f6ac0713e5b38
Y= 0xa39a28c59ff7f796b85223b8834384907c626086415487288ed1182ca4487dc1
    ae5f37af90fd267b7c0dc8542ea52cd984af54731bc84271d6186d973c91359b
U= 0x3c80e89805380f52cf86ff990501801d70e5b4636e8478674d2d5706a56a666
    63eb03abdc332584f7ea8c3255b1be3ca75e4685a060e0ea88e569612d9e7227
V= 0xd8f2cf17c484f4bb6a0208b3796a2609971c55d56bffadf155c0bf76f7afe99
    7d6b6e8fde9e2cefd0ab3e31a1862953425a70334e4e2404c9cd9079856c7259
```

SEED:

```
03 8a 01 b5 ea a2 28 3b bb 29 7b 81 ad 94 92 01
e4 32 11 df 76 a3 70 ec c0 09 ec 49 1f 9f 8d 33
f2 ee 24 08 c7 88 27 cd 0c 51 17 a7 e3 8d 58 5b
3d 15 50 30 a3 29 1b ad 6a 21 ab 48 38 1d 66 bc
1b d6 b9 ba 6e d8 6a 21 65 c5 99 84 dc 5d 51 81
f3 f1 97 fe 4a 86 81 c2 e5 0a 22 a0 61 2c 55 7e
```

Point Q_2

```
X= 0xb3e6c475f173af4494dd02ad7c9df3bd6a5ca82c3d65ad86fb330dfb1c40e34
    c4cd04d93f609cff2daea5907d0e08192a29be3ff27522223b868e8bcc6a7b74
Y= 0x53ffcf818281bcf383d9b6542b3b1fce5bd20cd1c805ed1dacb83ba161167a5
    eb96df52c1d290496043ea514c465ecb37970fc7ffbb6ca35a767cd0227fe8c
U= 0x8dd3f6f455ffaea85c3935750792b65fa1ba990c7ac8bc449a77bb86aeb87eb6
    ecb6bf387924885b0ea1e30fc4d742919504cd7baf4926b777ed40b898be41f8
V= 0x2d7edc1ca6078878d2d8ecafabc2abc83fcbb69c049baa11951ff2523b69b1d1
    4ee6c0fa7cbd5a566cb32246d14568eb9fa04e3b53ee6175bb32887796870ba9
```

SEED:

```
63 ce db 44 3d f8 df 68 8d 5d fd d0 ea 54 41 62
f5 6d 78 92 73 0c 86 88 53 e2 24 4d dd 87 1e 4a
0e 3f b7 32 40 c8 7a bc e8 fd b3 16 dd 0e 9b 23
ec 1f c7 40 86 29 8c fc f2 a1 d9 18 31 af a3 cf
```

```

1e 98 b8 0d 42 0c f6 73 8d 57 44 77 8e 1a d3 e4
42 d7 26 39 6c 91 b7 f5 e8 84 09 8d be 02 aa 80
Point Q_3
X= 0xbe963ad90f84ff9ff6ff7ddd39d91cea649e849bf20b8cc1e72040cf689a974f
        40f24e10c737bfa558b514c605b7c156e24251b859202b12ef311b0f363171eb
Y= 0x007cfa56f5ae239694e74f7996e1f44fc4f62205a555fdb627e4212576b4591
        7f88667bcd924a3271f40dc4bbd2f2e216b4fcf59c25fdd8154241d40f42e2ad
U= 0xff6697883ce5c6cc165fa78ff158c03b31add23dc01b24902b18c5487f1835ff
        eaf4af5ede44f8b254748704e504810597d0e4418daf50e0253f33915de97b7b
V= 0x54e1ba656234479c5845c06af70bbe741a863d5186ca720ee2f43bdd4d5b74
        71594871d532ce263928aa30ae3c25efc6a2f82d4163c45869339426888be3bc
SEED:
06 ce 08 fa 5d 11 50 45 e2 d2 a8 03 01 d2 9e 2a
39 c3 ea e7 f1 61 37 f9 3e 51 d1 46 f3 21 b1 89
fb 5c 17 70 26 5b 30 8b 6d f2 87 7c d9 d3 6f 8a
3c b4 e7 1d f0 99 a4 73 69 1d d5 46 8d 43 50 f9
87 df e5 e5 de ff 3c 7b b8 f4 62 ed 19 9b f3 33
7a 6f f9 0e c5 f0 bc bb 1a 59 1e cd c2 9b 52 64

```

A.2. Test examples

This protocol implementation uses the GOST R 34.11-2012 hash function (see [RFC6986]) with 256-bit output as the H function and the HMAC_GOSTR3411_2012_512 function defined in [RFC7836] as a PRF function for the F function. The parameter len is considered equal to 256, if $2^{254} < q < 2^{256}$, and equal to 512, if $2^{508} < q < 2^{512}$.

The test examples for one of the three points of each curve in Appendix A.1 of this document are given below.

A.2.1 Curveid-GostR3410-2001-CryptoPro-A-ParamSet

The input protocol parameters in this example take the following values:

```

N= 3
ind= 1
ID_A:
 00 00 00 00
ID_B:
 00 00 00 00
PW:
 31 32 33 34 35 36 ('123456')
salt:
 29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
Q_ind:
 X= 0xa33ce065b0c23e1d3d026a206f8a1f8747ed1cd92a665bf85198cdb10ac90a5c
 Y= 0xb00d0dc0733883f05de9f55fd711f55998f5508cc40bead80c913b4d5b533667
The function F (PW, salt, 2000) takes the following values:
F(PW,salt,2000):

```

```
bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
```

The coordinates of the point Q_PW are:

X= 0xd339b3396ae4a816388a14c79ab3a8dd495fa4c53f0d4076579022ef2aaeb68

Y= 0xdad91482e208590fd316bf959480f5ec2c17463ec8fc8f63030649b452cddda8

During the calculation of the message u_1 on the subject A the parameter alpha, the point alpha*P and the message u_1 take the following values:
alpha=0xfcdb45d1f2538097d5a031fa68bbb43c84d12b3de47b7061c0d5e24993e0c87
alphaP:

```
X= 0x24538e096781b9d53316c342ae5bbd49ccfb2db627c3659175bc4fa9d95b4618
```

```
Y= 0xf6e39a7490ae0ac449f5abe7e2135697c582daf3a038c40a05e6e8be3e466a2b
```

u_1:

```
X= 0xcf73b30dd577369fb98e2a93d6d98d7450f9ceef2badale3dcbb1016dff1e1
```

```
Y= 0x1cf05014caedb1635120b30e0a445060b8f1cca52965cf83c4838d554ca4e2
```

During processing a message u_1, calculation the K_B key and the message u_2 on the subject B the parameters betta, src, K_B = HASH (src), betta*P and u_2 take the following values:

betta=0xf2144faddc497d9ef6324912fd367840ee509a2032aedb1c0a890d133b45f596

src:

```
39 c0 e8 83 59 91 cd 6d 56 88 fc ad 55 29 1f 79
e5 0f 87 9d 94 b5 0a b2 db d6 bd f7 e8 39 b7 1a
10 b5 a7 8d c0 36 b8 73 f7 e4 b1 6b 12 48 6f eb
69 d7 39 d4 01 4d ae e2 cc 5c 2f c7 4a 2c c8 06
```

K_B:

```
e0 4e e0 14 7f 9f 19 8d e2 5a af 33 a2 84 99 e0
ce 7d 31 6e 47 39 76 2f d5 19 f8 e9 91 d7 fc 00
```

betta*P:

```
X= 0xb11f1a8fb043bc6d4068667b897e4ff637b8410f5eb19e11b0a7028f34d6936a
```

```
Y= 0x266d952955e2ab3f3ba75d14a919795d6b8ac04dbcff1cfaac6ba32291c099fd
```

u_2:

```
X= 0x6e1fb24b6131a3ad0b60e477a38715c6f96f21bb0b2f9ebd67680e804a77199
```

```
Y= 0x873ee3c546c41e8f707298f11b955fe64f7577d52d7dadc1beccb9925178ca80
```

During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:

K_A:

```
e0 4e e0 14 7f 9f 19 8d e2 5a af 33 a2 84 99 e0
ce 7d 31 6e 47 39 76 2f d5 19 f8 e9 91 d7 fc 00
```

The message MAC_A=HMAC (K_A, 0x01 || ID_A || ind || salt || u_1 || u_2) from the subject A takes the following value:

MAC_A:

```
bd 35 c5 0e 90 60 e6 4f 04 2e 7b e6 cc 02 99 84
0c 8e 27 82 b8 e5 9c 3d d4 47 50 11 16 73 c5 ea
```

The message MAC_B=HMAC (K_B, 0x02 || ID_B || ind || salt || u_1 || u_2) from the subject B takes the following value:

MAC_B:

```
c8 c8 2c 0f ed 8e 4d 1e 41 42 d7 a9 f0 55 b4 5f
f6 71 2d 2f 41 bf 26 ef 2f bc 37 c5 56 4b 86 d3
```

A.2.2 Curveid-GostR3410-2001-CryptoPro-B-ParamSet

The input protocol parameters in this example take the following values:

N= 3
 ind= 1
 ID_A:
 00 00 00 00
 ID_B:
 00 00 00 00
 PW:
 31 32 33 34 35 36 ('123456')
 salt:
 29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
 Q_ind:
 X= 0x0ad754474a915d9d706c6b8dc879858a1cb85cc8f6c148fc3120825393ecd394
 Y= 0x68c33b6d0343cf72cb19666ffd487fa94294dc677b28c8e27ec36068ff85ed83

The function F (PW, salt, 2000) takes the following values:

F(PW,salt,2000):
 bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
 d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67

The coordinates of the point Q_PW are:

X= 0x7a7211a430fd4e31b815e6d2454eea9574f034c5c442dce1723d69555d3ee4c9
 Y= 0x2995e857187808e80d3e40a00fb87128e203f2d91c1f15d8193a5aad95964734

During the calculation of the message u_1 on the subject A the parameter alpha, the point alpha*P and the message u_1 take the following values:

alpha=0x499d72b90299cab0da1f8be19d9122f622a13b32b730c46bd0664044f2144fad
 alphaP:

X= 0x61d6f916db717222d74877f179f7ebef7cd4d24d8c1f523c048e34a1df30f8dd
 Y= 0x3ec48863049cfcf662904082e78503f4973a4e105e2f1b18c69a5e7fb209000

u_1:
 X= 0x35e78fcbe24998eb3039445a9de7032aadf291e7768196ef618e45bed80edf88
 Y= 0x1970a4697295f6d361d2c3edd3885794c1254bac3f4adb4a3346ad01a911d13c

During processing a message u_1, calculation the K_B key and the message u_2 on the subject B the parameters betta, src, K_B = HASH (src), betta*P and u_2 take the following values:

betta=0x0f69ff614957ef83668edc2d7ed614be76f7b253db23c5cc9c52bf7df8f4669d
 src:

50 14 0a 5d ed 33 43 ef c8 25 7b 79 e6 46 d9 f0
 df 43 82 8c 04 91 9b d4 60 c9 7a d1 4b a3 a8 6b
 00 c4 06 b5 74 4d 8e b1 49 dc 8e 7f c8 40 64 d8
 53 20 25 3e 57 a9 b6 b1 3d 0d 38 fe a8 ee 5e 0a

K_B:
 a6 26 de 01 b1 68 0f f7 51 30 09 12 2b ce e1 89
 68 83 39 4f 96 03 01 72 45 5c 9a e0 60 cc e4 4a

betta*P:
 X= 0x33bc6f7e9c0ba10cfb2b72546c327171295508ea97f8c8ba9f890f2478ab4d6c
 Y= 0x75d57b396c396f492f057e9222ccc686437a2aad464e452ef426fc8eed1a4a6

u_2:
 X= 0x20d7a92b238143e3f137be904d52fa35c45a29f02a7226a7ac83a1172c2a55cd

$Y = 0x5fc4cd6ffb0e76ea8603ce9e6dab5164285617969ab3bfab09fbebe8595d1f47b$
 During processing a message u_2 and calculation the key on the subject A
 the K_A key takes the following value:

K_A :

```
a6 26 de 01 b1 68 0f f7 51 30 09 12 2b ce e1 89
68 83 39 4f 96 03 01 72 45 5c 9a e0 60 cc e4 4a
```

The message $MAC_A = \text{HMAC}(K_A, 0x01 || ID_A || \text{ind} || \text{salt} || u_1 || u_2)$
 from the subject A takes the following value:

MAC_A :

```
55 7a 59 61 42 60 39 a1 52 c8 23 a7 65 04 59 b0
62 be 3d 47 56 53 03 09 95 57 1c e7 53 40 26 47
```

The message $MAC_B = \text{HMAC}(K_B, 0x02 || ID_B || \text{ind} || \text{salt} || u_1 || u_2)$
 from the subject B takes the following value:

MAC_B :

```
3b c5 5e 27 07 84 19 94 c4 b9 ca ba 43 e6 ce 6a
09 2d e9 08 83 76 5f b6 c3 44 c6 1d 76 02 96 e9
```

A.2.3 Curveid-GostR3410-2001-CryptoPro-C-ParamSet

The input protocol parameters in this example take the following values:

$N = 3$

$\text{ind} = 1$

ID_A :

```
00 00 00 00
```

ID_B :

```
00 00 00 00
```

PW :

```
31 32 33 34 35 36 ('123456')
```

salt :

```
29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
```

Q_{ind} :

```
X= 0x339f791f62938871f241c1c89643619aa8b2c7d7706ce69be01fddff3f840003
```

```
Y= 0x31d6d9264cc6f8fe09bf7aa48910b4ad5ddf74a2ef4699b76de09ffed295f11
```

The function $F(PW, \text{salt}, 2000)$ takes the following values:

$F(PW, \text{salt}, 2000)$:

```
bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
```

The coordinates of the point Q_{PW} are:

```
X= 0x8b666917d42c455331358c50c3c12c85b898a2e454b50dd773541da02e1c3068
```

```
Y= 0x8a9b6c4703934b7f0dc903f52c16275e1d38b568117c7cff3bd322a99a311fe9
```

During the calculation of the message u_1 on the subject A the parameter
 α , the point $\alpha * P$ and the message u_1 take the following values:

$\alpha = 0x3a54ac3f19ad9d0bleac8acdcea70e581f1dac33d13feaf81e762378639c1a8$

$\alpha * P$:

```
X= 0x96b7f09c94d297c257a7da48364c0076e59e48d221cba604ae111ca3933b446a
```

```
Y= 0x54e4953d86b77ecceb578500931e822300f7e091f79592ca202a020d762c34a6
```

u_1 :

```
X= 0x2124a22e00b1be2114f5ca42d58d55a0a9f2b08f8cb10275eddf8243402abb7a
```

```
Y= 0x62497815861d15877b7ad2e86768a2deb0f755a8b1a8897fc5235da783914a59
```

During processing a message u_1 , calculation the K_B key and the message u_2 on the subject B the parameters betta, src, $K_B = \text{HASH}(\text{src})$, betta^*P and u_2 take the following values:

$\text{betta}=0x448781782bf7c0e52a1dd9e6758fd3482d90d3cfccf42232cf357e59a4d49fd4$
 $\text{src}:$

```
16 a1 2d 88 54 7e 1c 90 06 ba a0 08 e8 cb ec c9
d1 68 91 ed c8 36 cf b7 5f 8e b9 56 fa 76 11 94
d2 8e 25 da d3 81 8d 16 3c 49 4b 05 9a 8c 70 a5
a1 b8 8a 7f 80 a2 ee 35 49 30 18 46 54 2c 47 0b
```

K_B :

```
be 7e 7e 47 b4 11 16 f2 c7 7e 3b 8f ce 40 30 72
ca 82 45 0d 65 de fc 71 a9 56 49 e4 de ea ec ee
```

betta^*P :

```
X= 0x4b9c0ab55a938121f282f48a2cc4396eb16e7e0068b495b0c1dd4667786a3eb7
Y= 0x223460aa8e09383e9df9844c5a0f2766484738e5b30128a171b69a77d9509b96
```

u_2 :

```
X= 0x47ad0110d1620fe38832e90b58971d2e0b9183dd52de23422b6fc47bec64541a
Y= 0x8296af496b3c52640e738a195d63ab7bfb457aba7c71b5649cc3e300829cbf0a
```

During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:

K_A :

```
be 7e 7e 47 b4 11 16 f2 c7 7e 3b 8f ce 40 30 72
ca 82 45 0d 65 de fc 71 a9 56 49 e4 de ea ec ee
```

The message $\text{MAC}_A=\text{HMAC}(K_A, 0x01 || ID_A || \text{ind} || \text{salt} || u_1 || u_2)$ from the subject A takes the following value:

MAC_A :

```
47 58 fa 64 9f 2e 31 3b f2 70 8b 76 a7 f7 a7 5a
37 ce 9e 7f 55 c3 fc 5a 55 77 e8 77 a7 a2 c1 ea
```

The message $\text{MAC}_B=\text{HMAC}(K_B, 0x02 || ID_B || \text{ind} || \text{salt} || u_1 || u_2)$ from the subject B takes the following value:

MAC_B :

```
2f 33 b9 bf f0 7d cd e3 44 67 bd b0 7f 62 fc a8
b3 52 3a 64 39 ef f1 c9 93 ba 0b 4c e6 c2 ed e4
```

A.2.4 Curveid-tc26-gost-3410-2012-512-paramSetA

The input protocol parameters in this example take the following values:

$N=3$

$\text{ind}=1$

ID_A :

```
00 00 00 00
```

ID_B :

```
00 00 00 00
```

PW :

```
31 32 33 34 35 36 ('123456')
```

salt :

```
29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
```

Q_{ind} :

```
X= 0x301aac1a3b3e9c8a65bc095b541ce1d23728b93818e8b61f963e5d5b13eec0fe
```

e6b06f8cd481a07bb647b649232e5179b019eef7296a3d9cfa2b66ee8bf0cbf2

Y= 0x191177dd41ce19cc849c3938abf3adaab366e5eb2d22a972b2dcc69283523e89
c9907f1d89ab9d96f473f96815da6e0a47297fcdd8b3adac37d4886f7ad055e0

The function F (PW, salt, 2000) takes the following values:

F(PW,salt,2000):

```
bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
1c 62 13 e3 93 0e fd da 26 45 17 92 c6 20 81 22
ee 60 d2 00 52 0d 69 5d fd 9f 5f 0f d5 ab a7 02
```

The coordinates of the point Q_PW are:

X= 0xa8b54a6339b296f5c5227670fb1482010b4b07e3642974b40c58a5f1da33370e
fed546eb17c6a707f3fc69671deba10a6de03a55f859473e9074a89b4a7b5488

Y= 0xfebf437ecf21536328b32f4c8e0430d5c0c096001c08a378ac30b8634412f44c
5ba9b7096642f51cc3a018cd1599c849cd62917a370eca3bbc6bed5eedabdd77

During the calculation of the message u_1 on the subject A the parameter alpha, the point alpha*P and the message u_1 take the following values:
alpha=0x3ce54325db52fe798824aead11bb16fa766857d04a4af7d468672f16d90e7396

046a46f815693e85b1ce5464da9270181f82333b0715057bbe8d61d400505f0e

alphaP:

X= 0xb93093eb0fcc463239b7df276e09e592fcfc9b635504ea4531655d76a0a3078e
2b4e51cfe2fa400cc5de9fbe369db204b3e8ed7edd85ee5cca654c1aed70e396

Y= 0x809770b8d910ea30bd2fa89736e91dc31815d2d9b31128077eedc371e9f69466
f497dc64dd5b1fad587f860ee256109138c4a9cd96b628e65a8f590520fc882

u_1:

X= 0xe8732d5471901b3eb9a31aaebeac7a6155c2c8fc1c960cb475e14074987dd2c8
4eccafac0835735a5c2df3d1c8dacf4a1d2e38e1e4419f5df4e25b7f8dd90b50

Y= 0xd680a41eaec979d49f4752008e9e92eb0efc1950d74b85e852be47f3958d5500
0442d859e5b459de5dc7acaa0c36383cd1f98f271333c6083dcecaf07ac825b8

During processing a message u_1, calculation the K_B key and the message u_2 on the subject B the parameters betta, src, K_B = HASH (src), betta*P and u_2 take the following values:

betta=0xb5c286a79aa8e97ec0e19bc1959a1d15f12f8c97870ba9d68cc12811a56a3bb1
1440610825796a49d468cdc9c2d02d76598a27973d5960c5f50bce28d8d345f4

src:

```
84 59 c2 0c b5 c5 32 41 6d b9 28 eb 50 c0 52 0f
b2 1b 9c d3 9a 4e 76 06 b2 21 be 15 ca 1d 02 da
08 15 de c4 49 79 c0 8c 7d 23 07 af 24 7d da 1f
89 ec 81 20 69 f5 d9 cd e3 06 af f0 bc 3f d2 6e
d2 01 b9 53 52 a2 56 06 b6 43 e8 88 30 2e fc 8d
3e 95 1e 3e b4 68 4a db 5c 05 7b 8f 8c 89 b6 cc
0d ee d1 00 06 5b 51 8a 1c 71 7f 76 82 ff 61 2b
bc 79 8e c7 b2 49 0f b7 00 3f 94 33 87 37 1c 1d
```

K_B:

```
53 24 de f8 48 b6 63 cc 26 42 2f 5e 45 ee c3 4c
51 d2 43 61 b1 65 60 ca 58 a3 d3 28 45 86 cb 7a
```

betta*P:

X= 0x238b38644e440452a99fa6b93d9fd7da0cb83c32d3c1e3cf5df5c3eb0f9db91
e588daedc849ea2fb867ae855a21b4077353c0794716a6480995113d8c20c7af

```
Y= 0xb2273d5734c1897f8d15a7008b862938c8c74ca7e877423d95243eb7ebd02fd2
    c456cf9fc956f078a59aa86f19dd1075e5167e4ed35208718ea93161c530ed14
```

u_2:

```
X= 0x1830804bf1fb07ebd43f27d03ff71ad9c7c31becaf1d3585dfb9e356c36638dc
    d82aba559dec06d46c862566653dfe0b116eb1a68439b0283f4d79ce48408eee
Y= 0x23b33ae97fba92e06095c41525aedf7b5d96fe9ca8e0244ed6c8a565d542d05e
    d3044cafbl8ac9a570c5133ba846d61da77f54da2daf13b0def7d90a0796f06
```

During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:

K_A:

```
53 24 de f8 48 b6 63 cc 26 42 2f 5e 45 ee c3 4c
    51 d2 43 61 b1 65 60 ca 58 a3 d3 28 45 86 cb 7a
```

The message MAC_A=HMAC (K_A, 0x01 || ID_A || ind || salt || u_1 || u_2) from the subject A takes the following value:

MAC_A:

```
37 e6 1a 43 2d 85 75 9b 30 13 a2 9d d6 82 f1 4d
    33 ca 86 89 37 db 4b f2 02 91 ed cf 6b e2 4b 4e
```

The message MAC_B=HMAC (K_B, 0x02 || ID_B || ind || salt || u_1 || u_2) from the subject B takes the following value:

MAC_B:

```
72 dc de 19 5f 26 4b b8 a8 1d 2a fe 2f d9 da 2d
    60 12 81 9c 15 f7 11 db 2b c4 c5 74 85 9e 05 3e
```

A.2.5 Curveid-tc26-gost-3410-2012-512-paramSetB

The input protocol parameters in this example take the following values:

N= 3
ind= 1
ID_A:
00 00 00 00
ID_B:
00 00 00 00
PW:
31 32 33 34 35 36 ('123456')
salt:
29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
Q_ind:

```
X= 0x488cf12b403e539fde9ee32fc36b6ed52aad9ec34ff478c259159a85e99d3dda
    dfd5d73606ecee351e0f780a14c3e9f14e985d9d7ddec93b064fc89b0c843650
Y= 0x7bc73c032edc5f2c74dd7d9da12e1856a061ce344a77253f620592752b1f3a3d
    cbbc87eb27ec4ed5e236dfcb03f3972404747e277671e53a9e412e82aaf6c3f7
```

The function F (PW, salt, 2000) takes the following values:

F(PW,salt,2000):

```
bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
    d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
    1c 62 13 e3 93 0e fd da 26 45 17 92 c6 20 81 22
    ee 60 d2 00 52 0d 69 5d fd 9f 5f 0f d5 ab a7 02
```

The coordinates of the point Q_PW are:

```
X= 0x2383039092052ed0e8ca3f751c11ebb891b8f32f7c66a437dec86345c63efc4b
```

a1ecd04dfc11826dd581cbc1d744754e284c00b04eef9cd6eff22c12432c46fd
 $Y = 0x374202580afbaef2f68da8a5c03ab82e71eb4c1f1fdd881aa2911d0206d470039$
 $275d298d5477901565ab826ec4492f67eebcf3194442f272fd2cad9a5f04234f$
 During the calculation of the message u_1 on the subject A the parameter alpha, the point $\alpha * P$ and the message u_1 take the following values:
 $\alpha = 0x715e893fa639bf341296e0623e6d29dadf26b163c278767a7982a989462a3863$
 $fe12aef8bd403d59c4dc4720570d4163db0805c7c10c4e818f9cb785b04b9997$
alphaP:
 $X = 0x10c479ea1c04d3c2c02b0576a9c42d96226ff033c1191436777f66916030d87d$
 $02fb93738ed7669d07619ffce7c1f3c4db5e5df49e2186d6fa1e2eb5767602b9$
 $Y = 0x039f6044191404e707f26d59d979136a831cce43e1c5f0600d1ddf8f39d0ca3d$
 $52fdb943bf04ddced1aa2ce8f5ebd7487acdef239c07d015084d796784f35436$
 u_1 :
 $X = 0x0ab9e56fc0d48e4982ee0a0b09507a63dc530181611d9f00d0464724415757b9$
 $de1c647178783a0fb4648df8e3dalefeb4db29de4711c8599191054ca7de6c4$
 $Y = 0x4decae941f8d19c44daae9eb132019e116478124e76430b8bee16ce6910a06c8$
 $a2fed68f4907e4ba17c4f4e3356dc3b3b8647165b9claae54b1c13239bfa8213$
 During processing a message u_1 , calculation the K_B key and the message u_2 on the subject B the parameters betta, src, $K_B = \text{HASH}(\text{src})$, $\text{betta} * P$ and u_2 take the following values:
 $\text{betta} = 0x30fa8c2b4146c2dbbe82bed04d7378877e8c06753bd0a0ff71ebf2bef8da8f3$
 $dc0836468e2ce7c5c961281b6505140f8407413f03c2cb1d201ea1286ce30e6d$
src:
 3f 04 02 e4 0a 9d 59 63 20 5b cd f4 fd 89 77 91
 9b ba f4 80 f8 e4 fb d1 25 5a ec e6 ed 57 26 4b
 d0 a2 87 98 4f 59 d1 02 04 b5 f4 5e 4d 77 f3 cf
 8a 63 b3 1b eb 2d f5 9f 8a f7 3c 20 9c ca 8b 50
 b4 18 d8 01 e4 90 ae 13 3f 04 f4 f3 f4 d8 fe 8e
 19 64 6a 1b af 44 d2 36 fc c2 1b 7f 4d 8f c6 a1
 e2 9d 6b 69 ac ce ed 4e 62 ab b2 0d ad 78 ac f4
 fe b0 ed 83 8e d9 1e 92 12 ab a3 89 71 4e 56 0c
 K_B :
 d5 90 e0 5e f5 ae ce 8b 7c fb fc 71 be 45 5f 29
 a5 cc 66 6f 85 cd b1 7e 7c c7 16 c5 9f f1 70 e9
 $\text{betta} * P$:
 $X = 0x34c0149e7bb91ae377b02573fcc48af7bfb7b16deb8f9ce870f384688e3241a3$
 $a868588cc0ef4364cca67d17e3260cd82485c202adc76f895d5df673b1788e67$
 $Y = 0x608e944929bd643569ed5189db871453f13333a1eaf82b2fe1be8100e775f13d$
 $d9925bd317b63bfaf05024d4a738852332b64501195c1b2ef789e34f23ddafc5$
 u_2 :
 $X = 0x66defd2a42f0efe38ed3d4a4dfbed6b86d40f4adf156c86fee1605dbf6b057b1$
 $2fe82a0be4823f7f215b5110673e02e3bf44f0ae26630005fcfd9f01473127eb$
 $Y = 0x36168c6d20c9514556ab442bf63ded0115346916ef45af7e5517f59205d1cc52$
 $ae2e72c3036f13cab7de12932e4a3acd0789f5e2474ff722b81334676c8a3371$
 During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:
 K_A :
 d5 90 e0 5e f5 ae ce 8b 7c fb fc 71 be 45 5f 29

a5 cc 66 6f 85 cd b1 7e 7c c7 16 c5 9f f1 70 e9
 The message MAC_A=HMAC (K_A, 0x01 || ID_A || ind || salt || u_1 || u_2)
 from the subject A takes the following value:

MAC_A:

```
9e c1 a8 74 93 b2 87 c9 ca c3 da c2 a2 d7 1b 82
8d c5 97 7c b0 03 93 42 c1 5a cd fb 66 c8 cf 89
```

The message MAC_B=HMAC (K_B, 0x02 || ID_B || ind || salt || u_1 || u_2)
 from the subject B takes the following value:

MAC_B:

```
a9 b2 f1 9b d9 c1 fd 0f 0c ab fd 09 52 94 c6 e6
3c d5 9f 12 cf 8e fd 01 12 46 0d b7 aa 20 bb 6e
```

A.2.6 Curveid-tc26-gost-3410-2012-256-paramSetA

The input protocol parameters in this example take the following values:

N= 3

ind= 1

ID_A:

```
00 00 00 00
```

ID_B:

```
00 00 00 00
```

PW:

```
31 32 33 34 35 36 ('123456')
```

salt:

```
29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
```

Q_ind:

```
X= 0x5161b08a973d521bdde0cbd45b68aa0470e1058dd936e5bd618fd3373770eed9
```

```
Y= 0xc1633db551677c62b9c2b69d47e503c0f8ca83b6b3109dece0a5f985d77a83a7
```

The function F (PW, salt, 2000) takes the following values:

F(PW,salt,2000):

```
bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
```

The coordinates of the point Q_PW are:

```
X= 0xa0fd0bcfaa07f640c802aa95f42e80b28bb758fbcb7ee2aca2cc0a615b567207
```

```
Y= 0x52cf0c960f362894bd097d198999e965bd940c7828e0d2ad38a0097f68135047
```

During the calculation of the message u_1 on the subject A the parameter alpha, the point alpha*P and the message u_1 take the following values:

alpha=0x147b72f6684fb8fd1b418a899f7dbeacf5fce60b13685baa95328654a7f0707f

alphaP:

```
X= 0x33fbac14eae538275a769417829c431bd9fa622b6f02427ef55bd60ee6bc2888
```

```
Y= 0x22f2ebcf960a82e6cdb4042d3ddda511b2fba925383c2273d952ea2d406eae46
```

u_1:

```
X= 0x8e8929226c7f679ea8c2dfb833d1f8062d62a9672493df02ad7462014c0edbc6
```

```
Y= 0x20f2382c2425aaa638f61e8b70fcf70dae6bcb2f9f341b33ae577c62395aa816
```

During processing a message u_1, calculation the K_B key and the message u_2 on the subject B the parameters betta, src, K_B = HASH (src), betta*P and u_2 take the following values:

betta=0x30d5cfadaa0e31b405e6734c03ec4c5df0f02f4ba25c9a3b320ee6453567b4cb

src:

```
a3 39 a0 b8 9c ef 1a 6f fd 4c a1 28 04 9e 06 84
df 4a 97 75 b6 89 a3 37 84 1b f7 d7 91 20 7f 35
11 86 28 f7 28 8e aa 0f 7e c8 1d a2 0a 24 ff 1e
69 93 c6 3d 9d d2 6a 90 b7 4d d1 a2 66 28 06 63
```

K_B:

```
7d f7 1a c3 27 ed 51 7d 0d e4 03 e8 17 c6 20 4b
c1 91 65 b9 d1 00 2b 9f 10 88 a6 cd a6 ea cf 27
```

betta*P:

```
X= 0x2b2d89fab735433970564f2f28cf1b57d640cb902bc6334a538f44155022cb2
Y= 0x10ef6a82eef1e70f942aa81d6b4ce5dec0ddb9447512962874870e6f2849a96f
```

u_2:

```
X= 0x47182ed8f018fa93a5d837e52724af6051c168ef15e4a40fe926473bc3f1032a
Y= 0x97f3e1e674da53b0ec3ebbla62a25c7424f4334950daec4d33045f78d9faeeb4
```

During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:

K_A:

```
7d f7 1a c3 27 ed 51 7d 0d e4 03 e8 17 c6 20 4b
c1 91 65 b9 d1 00 2b 9f 10 88 a6 cd a6 ea cf 27
```

The message MAC_A=HMAC (K_A, 0x01 || ID_A || ind || salt || u_1 || u_2) from the subject A takes the following value:

MAC_A:

```
f5 69 f6 e7 68 9e f0 ba 08 46 98 cc 0e bc ac 59
67 8c 93 26 af 21 f5 4d 3e 90 05 29 32 6b 41 ee
```

The message MAC_B=HMAC (K_B, 0x02 || ID_B || ind || salt || u_1 || u_2) from the subject B takes the following value:

MAC_B:

```
80 d5 f0 3b 48 22 37 76 43 b4 ff 92 05 dd ed b1
9f 22 80 1f b4 de 0b fb e0 74 55 c2 54 32 45 1e
```

A.2.7 Curveid-tc26-gost-3410-2012-512-paramSetC

The input protocol parameters in this example take the following values:

N= 3

ind= 1

ID_A:

```
00 00 00 00
```

ID_B:

```
00 00 00 00
```

PW:

```
31 32 33 34 35 36 ('123456')
```

salt:

```
29 23 be 84 e1 6c d6 ae 52 90 49 f1 f1 bb e9 eb
```

Q_ind:

```
X= 0x5b065ead2e94de0ee2e462de204c93c6b2bf3498ad920393cb60259e1a8ffc7c
7e7d4defa20ff4282abf70207e4611d532f40db6800e29d2b53f6ac0713e5b38
```

```
Y= 0xa39a28c59ff7f796b85223b8834384907c626086415487288ed1182ca4487dc1
ae5f37af90fd267b7c0dc8542ea52cd984af54731bc84271d6186d973c91359b
```

The function F (PW, salt, 2000) takes the following values:

F(PW,salt,2000):

```

bd 04 67 3f 71 49 b1 8e 98 15 5b d1 e2 72 4e 71
d0 09 9a a2 51 74 f7 92 d3 32 6c 6f 18 12 70 67
1c 62 13 e3 93 0e fd da 26 45 17 92 c6 20 81 22
ee 60 d2 00 52 0d 69 5d fd 9f 5f 0f d5 ab a7 02

```

The coordinates of the point Q_PW are:

```

X= 0x463e9d38239ddac18e7cc7f6caa7244ae5c49d58dcdf6a56510d7779496744d
    75e3e0d5795d4e603f7baea8d24ada989d4179e1db33d1912602fc59470192df
Y= 0x088874b12c160930aa840f046ee75fa86206f19ca5f431d81e2381d6d947b7b0
    30577e40f09b1c16f8e6ef84daddba028f8b6e397a27ece0e13197662659af4d

```

During the calculation of the message u_1 on the subject A the parameter alpha, the point alpha*P and the message u_1 take the following values:

```

alpha=0xb3fe942126aefc0287f82c6290505aeb117aa8dcb033cee56222dd1b9f9e1e5
    377583ba300211ec2c399546b4f54578ee925c238d52530c159c7034ccfa0ddd
alphaP:

```

```

X= 0x61427a12468974b5829de1263d91fdfd8e26ea337c6c223595e05b4da4f8fe93
    2b532f33c0f4631729422c04f7018a7bf619c026ef0edc4ba2a96b79397eba92
Y= 0x6833806e26791ef1dd01e60c10cc247173b97d7d8d7fea53de4a8a6a444bacc7
    042bf35394aef4cfde0f236788f2e9fc9e10f7d7fee54fff951ae17996808c1

```

u_1:

```

X= 0x03664ef83e51beaec1f11711f8742b180001c7734a715e4a693758acd9851b38
    c6d7e0a316d809b75694ae1b356951a93c91a9b85aa3e3a561742211fd238852
Y= 0x2b92fa93fab060fa86c3039eb2904bc18cbe45032dc3c93ce1c6ba1542a29e0d
    790a5f7b63928ed9e50d1fefd6bd00ade4eb021bc62a560567a3419e74dfc08a

```

During processing a message u_1, calculation the K_B key and the message u_2 on the subject B the parameters betta, src, K_B = HASH (src), betta*P and u_2 take the following values:

```

betta=0xd494d54fb777781d1324ed6088bb0d9d86b8b0a252aa6a3ee70af8ef44b87a6
4cea3a432b61a699bad2d9760d700c2891b6285be0b0bb90f16a40a9b2e0e36a
src:

```

```

c2 a3 1a 15 08 52 8a fb 70 be d5 7a 3a 97 9a 3a
8c ed 00 2f 1b 05 8f 99 cb ee 64 56 5c cb ae 42
c5 80 b1 39 18 04 b3 e3 34 d0 2f 70 55 18 ef 16
b7 cf 0e 79 91 76 6f 7e 22 81 f2 87 b1 df cd 34
5c 56 04 ef 1d 9a 8e b8 27 3f 2e 7a 3b fb a4 13
ad 7f 19 59 99 41 f8 f6 73 63 2b e1 43 b1 65 7f
d3 3a 3a de 7d 9f 71 6c e4 0c b5 9e 9d dd a5 0d
db 87 66 57 e7 37 8f f1 55 94 fc 7a 9e 4b 03 48

```

K_B:

```

84 14 e1 12 6c 56 a1 1e 1f 5e a0 b7 c3 bd ab e9
8b 26 8b 59 d4 08 f9 7c d0 ea d7 c2 7e e4 9c 15

```

betta*P:

```

X= 0xe247677c90ac3c74952c70da0d43f25ece4ac22eda732f7ddd772de7c3e69b22
    f7679cc01cae009e442c630c7aa9403a9f11e0fb62cf7af84e77b95210a17edd
Y= 0x63be6dc920e57cb1c5b63fd8b623db6c934b87e0b14468de32c9387515cf3d35
    618e945a986424708ef0515ccaa30061ac6870ab56c29c43340736a6c6179c2e

```

u_2:

```

X= 0x32260df3ddeabaa9c5c1f55248e8e9a3552cef81a19f0ac1e10f3b7280a844c
    5362b527dalc6ec7eeace2a77aa1167f5e18a4bb6bc6445b4f479ca239245002

```

Y= 0x04e0612a0c8cd4323535899d0698dd09bb9fc4302016f1b236c86692358ffd98
1cd082c0129763bd4749ee5bb014255d1de0fd7775deccb564213ebc7100001d

During processing a message u_2 and calculation the key on the subject A the K_A key takes the following value:

K_A:

84 14 e1 12 6c 56 a1 1e 1f 5e a0 b7 c3 bd ab e9
8b 26 8b 59 d4 08 f9 7c d0 ea d7 c2 7e e4 9c 15

The message MAC_A=HMAC (K_A, 0x01 || ID_A || ind || salt || u_1 || u_2) from the subject A takes the following value:

MAC_A:

53 0b 77 63 c5 9e 7c 98 52 59 ad eb af a4 16 41
c6 f4 35 47 85 01 bd c9 7e a9 cf 88 a6 9a 12 8c

The message MAC_B=HMAC (K_B, 0x02 || ID_B || ind || salt || u_1 || u_2) from the subject B takes the following value:

MAC_B:

3f 48 65 b8 8c 81 e5 ac 56 1e 31 c1 b3 d1 d9 0c
57 e1 e7 4b ac 77 b1 63 ac 60 74 82 4e 99 d3 cc

Authors' Addresses

Stanislav Smyshlyayev (editor)

CRYPTO-PRO

18, Suschevsky val

Moscow 127018

Russian Federation

Phone: +7 (495) 995-48-20

Email: svs@cryptopro.ru

Evgeny Alekseev

CRYPTO-PRO

18, Suschevsky val

Moscow 127018

Russian Federation

Phone: +7 (495) 995-48-20

Email: alekseev@cryptopro.ru

Igor Oshkin
CRYPTO-PRO
18, Suschevsky val
Moscow 127018
Russian Federation

Phone: +7 (495) 995-48-20
Email: oshkin@cryptopro.ru

Vladimir Popov
CRYPTO-PRO
18, Suschevsky val
Moscow 127018
Russian Federation

Phone: +7 (495) 995-48-20
Email: vpopov@cryptopro.ru