L2TP or not L2TP?

Alain Durand, ???

L2TP Configuration Latency (in authenticated mode)

- L2TP (8), PPP+CHAP (11), DHCPv6 (4) = **23 pkts**
- Idea: collapse all those layers into 1 protocol with minimum packet exchange. E.g.:
 - TSP:
 - 10 packets (digest-md5 auth)
 - TSP-lite:
 - 6 is possible
 - STEP:
 - 4 is possible

L2TP Configuration Latency (in non-authenticated mode)

- L2TP (8), PPP (8), DHCPv6 (2) = 18 pkts
- Idea: collapse all those layers into 1 protocol with minimum packet exchange. E.g.:
 - TSP:
 - 7 packets (anonymous)
 - TSP-lite:
 - 2 is possible, 3 with return reachability test
 - STEP:
 - 2 is possible

L2TP Encapsulation Overhead

- IPv6 over PPP (4)/L2TP (8)/UDP (8)/IPv4 (20) = 40 bytes
- Idea: collapse into:
 - IPv6/IPv4 = 20 bytes or IPv6/UDP/IPv4 = 28 bytes
- Case sudy: VoIP over radio link
 - VoIP payload = 44 bytes, radio overhead = 12 bytes
 - Total packet size:
 - With L2TP encapsulation: 44+8+40+40 +12 = 144 bytes
 - With IPv6/IPv4 encapsulation: 44+8+40+20+12 = 124 bytes (16% less)

What else will change by collapsing the layers of L2TP?

- PPP is doing MTU adaptation
- L2TP is doing the management of the tunnel (e.g. keep alive)
- L2TP can make sure packets are ordered
- If we do not use L2TP, the node may have to do all that.